



***StreamStor Real-Time Storage
Controller***

SDK 7.2

User's Guide

Copyright and Trademarks

The information in this document is subject to change without notice.

This document contains proprietary information that is protected by copyright. All rights are reserved. No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent of Conduant Corporation.

Printed in the United States.

© 2005 Conduant Corporation. All rights reserved.

StreamStor is a trademark of Conduant Corporation.

All other trademarks are the property of their respective owners.

Publication date: November 8, 2005

Table of Contents

Copyright and Trademarks	3
License Agreement and Limited Warranty	9
Chapter 1 Introduction	11
The StreamStor Software Development Kit	12
Installing the Software.....	12
Software Components.....	13
<i>Device Driver</i>	13
<i>Windows Uninstall</i>	13
<i>Windows Configuration/Test Utility</i>	13
<i>Windows Fetch Utility</i>	15
<i>Windows Library</i>	18
<i>Linux Uninstall</i>	18
<i>Linux Configuration/Test Utilities</i>	19
<i>Linux Library</i>	20
<i>Data Structures</i>	22
Chapter 2 Function Reference	23
XLRApiVersion.....	24
XLRAppend.....	25
XLRArmFPDP.....	27
XLRBindInputChannel.....	28
XLRBindOutputChannel.....	29
XLRCardReset.....	31
XLRClearChannels	32
XLRClearWriteProtect.....	33
XLRClose	34
XLRDeleteAppend	35
XLRDeviceFind	37
XLRDismountBank.....	38
XLREdit	39
XLREditData.....	40
XLERase.....	42
XLRGetBankStatus	45
XLRGetBaseAddr.....	46
XLRGetBaseRange.....	47
XLRGetDBInfo	48
XLRGetChassisType	49
XLRGetDeviceInfo.....	50
XLRGetDeviceStatus	51
XLRGetDirectory	52
XLRGetDriveInfo	53
XLRGetErrorMessage	54
XLRGetEvents.....	55
XLRGetEventsLength	57
XLRGetFIFOLength	58
XLRGetLabel	59
XLRGetLastError.....	60

XLRGetLength.....	61
XLRGetLengthLowHigh.....	62
XLRGetLengthPages.....	63
XLRGetMode.....	64
XLRGetPartitionInfo.....	65
XLRGetPlayLength.....	66
XLRGetSystemAddr.....	67
XLRGetUserDir.....	68
XLRGetUserDirLength.....	70
XLRGetVersion.....	71
XLRGetWindowAddr.....	72
XLRMountBank.....	73
XLRNetOpen (<i>Windows Only</i>).....	74
XLROpen.....	76
XLRPartitionCreate.....	77
XLRPartitionSelect.....	78
XLRPlayback.....	79
XLRRead.....	83
XLRReadData.....	84
XLRReadFifo.....	85
XLRReadImmed.....	86
XLRReadStatus.....	88
XLRReadToPhy.....	90
XLRRecord.....	91
XLRRecoverData.....	92
XLRReset.....	94
XLRRetrieveEvents.....	95
XLRSelectBank.....	97
XLRSelectChannel.....	99
XLRSelfTest.....	100
XLRSetBankMode.....	102
XLRSetDBMode.....	104
XLRSetDriveStandbyMode.....	106
XLRSetLabel.....	108
XLRSetMode.....	110
XLRSetPlaybackLength.....	111
XLRSetPortClock.....	113
XLRSetReadLimit.....	114
XLRSetUserDir.....	115
XLRSetWriteProtect.....	117
XLRStop.....	119
XLRTruncate.....	120
XLRWrite.....	122
XLRWriteData.....	124
Structure S_BANKSTATUS.....	125
Structure S_DBINFO.....	127
Structure S_DEVINFO.....	128
Structure S_DEVSTATUS.....	129
Structure S_DIR.....	131
Structure S_DRIVEINFO.....	132
Structure S_PARTITIONINFO.....	133
Structure S_READDESC.....	134

Structure S_XLRSWREV	135
Chapter 3 PCI Integration.....	137
PCI Integration.....	138
<i>Initialization and Setup</i>	138
<i>PCI Bus Interfacing</i>	138
<i>Multi-Card Operation</i>	139
Chapter 4 Operation	141
Operation	142
<i>Data Recording</i>	142
Recording Data	142
Data Wrap	143
Ending the Recording.....	143
<i>Data Read</i>	143
Read Setup.....	144
Read Positioning.....	144
Reading Data.....	144
Chapter 5 External Port.....	145
External Port.....	146
FPDP	147
<i>Overview</i>	147
<i>Interface Electronics</i>	147
<i>Data Formats</i>	148
<i>PIO Signals</i>	148
<i>Interface Functions</i>	148
<i>PSTROBE/PSTROBE* and STROB Signals</i>	149
Chapter 6 Channel Description and Selection	151
Channel Description and Selection	152
<i>Channel Description</i>	152
<i>Selecting an Operating Mode</i>	152
<i>Binding and Selecting Channels</i>	153
<i>Example 1</i>	153
<i>Example 2</i>	155
<i>Example 3</i>	156
Chapter 7 Bank Switching.....	159
Bank Switching.....	160
<i>Setting Bank Mode</i>	160
<i>Selecting a Bank</i>	161
<i>Recording a Drive Module</i>	161
<i>Playing back from a Drive Module</i>	162
<i>Labeling Drive Modules</i>	162
<i>Writing a User Directory</i>	163
<i>The Length of Drive Modules</i>	163
<i>Write Protecting Drive Modules</i>	164
<i>Erasing Drive Modules</i>	164
<i>Getting Bank Status</i>	164
<i>Replacing a Drive Module</i>	164
Chapter 8 Drive Partitioning.....	167
Drive Partitioning	168
<i>Creating a Partition</i>	168
<i>Selecting a Partition</i>	168
<i>Getting Partition Information</i>	169
<i>Bank Mode and Partitioning</i>	169
<i>Recording using Partitions</i>	170
<i>Removing Partitioning</i>	170

<i>Resizing Partitions</i>	170
<i>Example</i>	170
Chapter 9 Forking and Passthru	175
Forking And Passthru	176
<i>Overview</i>	176
<i>Forking</i>	176
<i>Passthru</i>	176
<i>Output over the PCI bus</i>	177
<i>Checking the FIFO length</i>	177
<i>Overflows</i>	177
Chapter 10 Technical Support	179
Technical Support.....	180
<i>Contacting Technical Support</i>	181
Appendix A – Error Codes.....	183

License Agreement and Limited Warranty

IMPORTANT: CAREFULLY READ THE TERMS AND CONDITIONS OF THIS AGREEMENT BEFORE USING THE PRODUCT. By installing or otherwise using the StreamStor Product, you agree to be bound by the terms of this Agreement. If you do not agree to the terms of this Agreement, do not install or use the StreamStor Product and return it to Conduant Corporation.

GRANT OF LICENSE. In consideration for your purchase of the StreamStor Product, Conduant Corporation hereby grants you a limited, non-exclusive, revocable license to use the software and firmware which controls the StreamStor Product (hereinafter the "Software") solely as part of and in connection with your use of the StreamStor Product. If you are authorized to resell the StreamStor Product, Conduant Corporation hereby grants you a limited non-exclusive license to transfer the Software only in conjunction with a sale or transfer by you of the StreamStor Product controlled by the Software, provided you retain no copies of the Software and the recipient agrees to be bound by the terms of this Agreement and you comply with the RESALE provision herein.

NO REVERSE ENGINEERING. You may not cause or permit, and must take all appropriate and reasonable steps necessary to prevent, the reverse engineering, decompilation, reverse assembly, modification, reconfiguration or creation of derivative works of the Software, in whole or in part.

OWNERSHIP. The Software is a proprietary product of Conduant Corporation which retains all title, rights and interest in and to the Software, including, but not limited to, all copyrights, trademarks, trade secrets, know-how and other proprietary information included or embodied in the Software. The Software is protected by national copyright laws and international copyright treaties.

TERM. This Agreement is effective from the date of receipt of the StreamStor Product and the Software. This Agreement will terminate automatically at any time, without prior notice to you, if you fail to comply with any of the provisions hereunder. Upon termination of this Agreement for any reason, you must return the StreamStor Product and Software in your possession or control to Conduant Corporation.

LIMITED WARRANTY. This Limited Warranty is void if failure of the StreamStor Product or the Software is due to accident, abuse or misuse.

Hardware: Conduant's terms of warranty on all manufactured products is one year from the date of shipment from our offices. After the warranty period, product support and repairs are available on a fee paid basis. Warranty on all third party materials sold through Conduant, such as chassis, disk drives, PCs, bus extenders, and drive carriers, is passed through with the original manufacturer's warranty. Conduant will provide no charge service for 90 days to replace or handle repair returns on third party materials. Any charges imposed by the original manufacturer will be passed through to the customer. After 90 days, Conduant will handle returns on third party material on a time and materials basis.

CHAPTER 1 : INTRODUCTION

Software: The warranty on all software products is 90 days from the date of shipment from Conduant's offices. After 90 days, Conduant will provide product support and upgrades on a fee paid basis. Warranties on all third party software are passed through with the original manufacturer's warranty. Conduant will provide no charge service for 90 days to replace or handle repair returns on third party software. Any charges imposed by the manufacturer will be passed through to the customer.

DISCLAIMER OF WARRANTIES. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CONDUANT CORPORATION DISCLAIMS ALL OTHER WARRANTIES AND CONDITIONS, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NONINFRINGEMENT, WITH REGARD TO THE STREAMSTOR PRODUCT AND THE SOFTWARE.

SOLE REMEDIES. If the StreamStor Product or the Software do not meet Conduant Corporation's Limited Warranty and you return the StreamStor Product and the Software to Conduant Corporation, Conduant Corporation's entire liability and your exclusive remedy shall be at Conduant Corporation's option, either (a) return of the price paid, if any, or (b) repair or replacement of the StreamStor Product or the Software. Any replacement Product or Software will be warranted for the remainder of the original warranty period.

LIMITATION OF LIABILITIES. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT SHALL CONDUANT CORPORATION BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, LOSS OF BUSINESS INFORMATION, OR ANY OTHER PECUNIARY LOSS) ARISING OUT OF THE USE OF OR INABILITY TO USE THE STREAMSTOR PRODUCT AND THE SOFTWARE. IN ANY CASE, CONDUANT CORPORATION'S ENTIRE LIABILITY UNDER ANY PROVISION OF THIS AGREEMENT SHALL BE LIMITED TO THE AMOUNT ACTUALLY PAID BY YOU FOR THE STREAMSTOR PRODUCT AND THE SOFTWARE. BECAUSE SOME STATES AND JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY, THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

RESALE. If you are authorized to resell the StreamStor Product, you must distribute the StreamStor Product only in conjunction with and as part of your product that is designed, developed and tested to operate with and add significant functionality to the StreamStor Product; you may not permit further distribution or transfer of the StreamStor Product by your end-user customer; you must agree to indemnify, hold harmless and defend Conduant Corporation from and against any claims or lawsuits, including attorneys' fees, that arise or result from the use or distribution of your product; and you may not use Conduant Corporation's name, logos or trademarks to market your product without the prior written consent of Conduant Corporation.

ENTIRE AGREEMENT; SEVERABILITY. This Agreement constitutes the complete and exclusive agreement between you and Conduant Corporation with respect to the subject matter hereof and supersedes all prior written or oral agreements, understandings or communications. If any provision of this Agreement is deemed invalid under any applicable law, it shall be deemed modified or omitted to the extent necessary to comply with such law and the remainder of this Agreement shall remain in full force and effect.

GOVERNING LAW. This Agreement is governed by the laws of the State of Colorado, without giving effect to the choice of law provisions therein. By accepting this Agreement, you hereby consent to the exclusive jurisdiction of the state and federal courts sitting in the State of Colorado.

Chapter 1

Introduction

The StreamStor Software Development Kit

One of the most powerful features of StreamStor is that it is an open platform device allowing other PCI devices complete access to record or read data from the disk storage. Conduant makes it easy for system designers to use StreamStor by providing the StreamStor Software Development Kit (SDK).

The SDK includes an Application Programming Interface (API) library. This library provides the control software for StreamStor in the form of DLLs (Dynamic Link Libraries) for Windows and an archive library for Linux that can be accessed by user application software. Application software can be developed in any environment capable of utilizing these library functions. This includes the various Windows programming languages such as Visual C++ and Visual Basic as well as graphical programming environments such as LabVIEW.

Installing the Software

Your StreamStor system was shipped with the Software Development Kit on CD-ROM. Please power up your computer. On Windows systems, when ready, run the `setup.exe` program on the CD-ROM to start the installation process. On Linux systems, refer to the file `linux/docs/install.txt` on the CD-ROM.

Plug and play operating systems such as Windows will detect the installation of the StreamStor board and attempt to configure the boards using the hardware plug and play wizard program. The required installation information file for plug and play installation is included on the CD-ROM. Make sure the plug and play wizard includes the CD-ROM drive in its search so that the StreamStor drivers will be properly installed. You should not cancel the plug and play wizard since this can create hardware conflicts in the system when using the StreamStor controller. Note that the `setup.exe` program must still be executed to install the StreamStor SDK onto your system.

The software installation procedure will install the device drivers, library files, example programs and all other components of the SDK onto your system.

The StreamStor SDK does not include software interfaces or drivers used for the control of data acquisition cards made by other manufacturers. However, it does include some sample programs to help in your software development efforts. Other drivers and examples may be available depending on your choice of data acquisition hardware. Contact Conduant support for more information.

Always review the `readme.html` file included with the SDK for the latest information not included in this manual.

Software Components

The SDK software components include operating system device drivers, support files, programming libraries and utility programs.

Device Driver


The StreamStor SDK provides device driver support for the Windows 2000, Windows XP and Linux operating systems. The drivers are installed automatically by the supplied setup program. On Windows systems, the device driver is named `windrvr6.sys`. The Linux device driver is installed as a kernel module named `windrvr6`. On Linux systems, refer to the file `linux/docs/install.txt` on the CD-ROM for driver installation instructions.

Windows Uninstall


The StreamStor SDK can be easily uninstalled in Windows by using the “Add/Remove Software” wizard in the control panel. Simply select “StreamStor SDK” and all installed components will be automatically removed. You can also select “Remove StreamStor SDK” in the StreamStor menu.

Windows Configuration/Test Utility

The utility program `sscfcfg.exe` is included with the SDK for testing the StreamStor system for proper configuration and functionality. If you have just received your StreamStor system or you are experiencing problems, running this program will perform a configuration and confidence test to insure that your system is working properly. The DLL file `bisrun.dll` is a required component. It should have been installed automatically into the installation directory. If `sscfcfg.exe` is moved, you must also move `bisrun.dll` to the same directory or to a Windows system directory. The initial `sscfcfg` screen will look something like this:



If more than one StreamStor is installed in your system there will be multiple choices in the card number pull down menu. After selecting the card number you must press the *Initialize* button to begin the process of finding, initializing and querying the StreamStor board for device information. If your board has been successfully configured, *Initialize* will enable the *Test* button and fill in the various device information fields. The `sscfg` screen should now appear similar to this:



If you encounter an error during initialization there may be damage to your system from shipping or the system has not been installed correctly. Please contact technical support for assistance.


If the initialization has completed successfully you should check the information provided by `sscfg` to insure your system has been correctly identified according to your purchased model and configuration. If you discover any problems please contact Conduant. At this point you should press the Test button to run a quick confidence test on the controller board and disk system.

⚠ CAUTION: *Running the confidence test in `sscfg` WILL overwrite any recorded data on StreamStor storage.*


If you get any error messages running this test please follow the instructions in the Troubleshooting section. If this test completes successfully, your StreamStor system is functioning normally.

Windows Fetch Utility

The utility program `ssfetech.exe` has been included to provide a basic tool for retrieving data from the StreamStor storage system-to-system disk files. The interface to `ssfetech` looks like this:



There are two options when using `ssfetech` to retrieve data, the first option is to simply retrieve a block of data to a single system file. The “Single File” button enables this mode and the filename specified is used as the destination for data retrieved from StreamStor. The current status of the recorder is displayed in the “Status” field and the “Available bytes” field indicates the length of data currently recorded on the device. The “Read From” box provides the controls for specifying the location and amount of data to be retrieved. The amount (File size) and address must be an increment of 4 bytes.



The second option for retrieving data is to use the “Multiple Files” option to automatically create system files of sequential and equal size data blocks from StreamStor. The directory field allows you to choose an alternate system directory (current directory will be used by default). The prefix and extension fields are used to define the common text for the filenames. The “Start #”, “End #” and “Digits” define a number used to form unique filenames. The “Start #” with the number of digits defined by “Digits” is appended to the prefix and the extension is appended after that (with a period) to form the filename. The “Filenames” area will show a preview of the file names to be used. The amount of data specified by “File size” is written to this file and the process is repeated with the number incrementing until “End #” is reached. The “Byte Address” for each retrieval is incremented by the file size amount so that sequential data is retrieved. This mode is useful for retrieving blocks of data into independent files when the size of the block is fixed such as when digital images have been recorded.

In both modes, the “Byte address” field is automatically incremented after each fetch by the amount of data transferred.

Windows Library

The software development kit includes a DLL library for integration of StreamStor into Windows based user applications. The required DLL file is `xlrapi.dll`. The library file `xlrapi.lib` is also included for linking the DLL functions to a user program. The required include files are `xlrapi.h`, `xlrtypes.h` and `xlrdbcommon.h`. Only the `xlrapi.h` file needs to be included in a user program. Example programs are included in the SDK. All of the include files are installed automatically by the installation software in the “Include” directory. The library file for linking user programs is installed in the “Lib” directory and the DLL is installed in the StreamStor installation directory.

Linux Uninstall

The StreamStor SDK can be easily uninstalled in Linux by removing the installation directory and the WinDriver module. To do so, enter the following commands as root where **<InstallDir>** is the full path name where the StreamStor SDK is installed and **<WinDriverModule>** is the name of the WinDriver module. The WinDriver module is `windrivr6`.

1. Remove the SDK installation directory as follows:

```
rm -rf <InstallDir>
```

For example, to remove the entire SDK:

```
rm -rf /usr/local/streamstor
```

2. Remove the WinDriver module as follows:

- a) Verify that the WinDriver module is not in use.

- b) Unload the WinDriver module by entering:

```
rmmmod <WinDriverModule>
```

- c) Remove the old device node by entering:

```
rm -rf /dev/<WinDriverModule>
```

- d) Remove the system startup file (if it exists) by entering:

```
rm -rf /etc/.windriver.rc
```

- e) Remove the user startup file (if it exists) by entering:

```
rm -rf $HOME/.windriver.rc
```

Linux Configuration/Test Utilities

Two Linux utility programs are included with the SDK to test the StreamStor system for proper configuration and functionality. If you have just received your StreamStor system or if you are experiencing problems, running these programs will perform configuration and confidence tests to insure that your system is working properly.

Linux programs that use the StreamStor SDK (such as the utilities below) require that the environment variable `STREAMSTOR_BIB_PATH` be set and exported to the SDK directory containing the StreamStor `*.bib` files. For example:

```
STREAMSTOR_BIB_PATH=/usr/local/streamstor/linux/bib
export STREAMSTOR_BIB_PATH
```

The program `ssopen` simply attempts to open the StreamStor and then closes it. To execute it:

1. `cd <InstallDir>/linux/util`
2. `./ssopen`

If your system can communicate with the StreamStor board, you should see this output:

```
Attempting to open StreamStor...
StreamStor opened successfully!
Device Status:
  SystemReady-> 1
  MonitorReady-> 0
  DriveFail-> 0
  DriveFailNumber-> 0
  SysError-> 0
  SysErrorCode-> 0
  CtlrError-> 0
```

The program `sstest` is similar to the Windows configuration test, `sscfcfg.exe`. It will attempt to initialize and configure the StreamStor and perform a confidence test. The confidence test will write data to the StreamStor storage and then will read that data.

⚠ CAUTION: *Running the confidence test `sstest` WILL overwrite any recorded data on StreamStor storage.*

To execute `sstest`:

CHAPTER 1 : INTRODUCTION

1. `cd <InstallDir>/linux/util`
2. `./sstest`

If the confidence test completes successfully, you should see output similar to the following:

```
*Getting Device Info
Board Type: PCI-816XF2
Serial Number: 5109
Number of drives: 8
Total Capacity: 320083329024

*Getting Version Info
API Version: 6.02
API Datecode: Oct 07 2005
Firmware Version: 11.14
Firmware Datecode: Oct 07 2005
Monitor Version: 6.02
XBAR Version: 3.20
ATA Version: 1.05
Ultra ATA Version: 0.00
Driver Version: 700

Processing Test Script
Script processing complete.

==== Starting Test ====

***Basic Confidence Test***
->Writing test pattern
->Write Completed

***Check Directory***
  Dir Length: 0x2000000
->Read/Compare Recorded Data
->Read/Compare Completed

***Basic Confidence Test Completed***
```

If you get any error messages running this test, please follow the instructions in the Troubleshooting section. If this test completes successfully your StreamStor system is functioning normally.

Linux Library

When the SDK is installed on a Linux system, a static function library is installed named `libssapi.a`. It contains all the StreamStor API functions. The required header files are `xlrapl.h`, `xlrtpes.h` and

CHAPTER 1 : INTRODUCTION

`xlrdbcommon.h`. Only the `xlrapi.h` file must be included by the user application. The library must be supplied to the linker to create a final executable program. An example C program that shows how to call the SDK library functions and a corresponding `gcc` makefile are in the directory `<InstallDir>/Linux/example`.

Data Structures

StreamStor API functions use the following structures. Refer to the end of the Function Reference section for details on each structure and its members.

S_BANKSTATUS	-	Bank status information
S_DBINFO	-	Daughter board information
S_DEVINFO	-	Device info parameters
S_DEVSTATUS	-	Device status flags
S_DIR	-	Recording directory
S_DRIVEINFO	-	Drive information
S_PARTITIONINFO	-	Drive Partitioning
S_READDESC	-	Parameters defining read requests
S_XLRWREV	-	Various device version strings

Chapter 2

Function Reference

XLRApiVersion

Syntax:

```
void XLRApiVersion( char *versionstring )
```

Description:

XLRApiVersion returns the API version as a string formatted as a *major.minor* version number.

Parameters:

- *versionstring* is a pointer to a character string to hold the returned version. It must be of minimum length XLR_VERSION_LENGTH.

Return Value:

The API version is returned in *versionstring*.

Usage:

```
/* Read XLR API version into string */  
char xlrstring[XLR_VERSION_LENGTH];  
  
XLRApiVersion( xlrstring );  
printf( "StreamStor API version is %s", xlrstring );
```

See Also:

XLRGetVersion.

XLRAppend

Syntax:

```
XLR_RETURN_CODE XLRAppend( SSHANDLE xlrDevice )
```

Description:

XLRAppend is used to restart a recording after it has been stopped. Data is appended to the existing recording.

If the StreamStor is in bank mode, data will be appended to the selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_READDESC       readDesc;
ULONG            myBuffer[40000];
XLR_RETURN_CODE  xlrReturnCode;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRRecord( xlrDevice, 0, 1 );
if( xlrReturnCode != XLR_SUCCESS )
    exit(1);

//
// Data transfer . . .
//
// Stop the record operation
XLRStop( xlrDevice );

// Read some data back
readDesc.AddrHi = 0;
readDesc.AddrLo = 0x120000;
readDesc.XferLength = sizeof( myBuffer );
readDesc.BufferAddr = &myBuffer;

xlrReturnCode = XLRRead( xlrDevice, &readDesc );
if( xlrReturnCode != XLR_SUCCESS )
    exit(1);
```

CHAPTER 2 : FUNCTION REFERENCE

```
//  
// Now start recording again without overwriting previous data  
//  
xlrReturnCode = XLRAppend( xlrDevice );  
if( xlrReturnCode != XLR_SUCCESS )  
    exit(1);
```

See Also:

XLRRecord, XLRSetBankMode and XLRSelectBank.

XLRArmFPDP

Syntax:

```
XLR_RETURN_CODE XLRArmFPDP( SSHANDLE xlrDevice )
```

Description:

XLRArmFPDP moves StreamStor from a ready to record state, to recording when an FPDP SYNC* pulse is received. StreamStor must already be in record mode, and SS_OPT_FPDP SYNCARM must be set. If no SYNC* pulse is received, no data will be recorded.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...

if( XLRAppend( xlrDevice ) != XLR_SUCCESS )
{
    exit(1);
}

if( XLRArmFPDP( xlrDevice ) != XLR_SUCCESS )
{
    exit(1);
}

// Waiting for SYNC pulse - data will be recorded to disk as soon
// as SYNC is received.
```

See Also:

XLRSetFPDPOption, XLRRecord and XLRAppend.

XLRBindInputChannel

Syntax:

```
XLR_RETURN_CODE XLRBindInputChannel( SSHANDLE xlrDevice, UINT
channel )
```

Description:

XLRBindInputChannel binds a channel for input INTO StreamStor. In other words, “input” is relative to StreamStor. To record on a particular channel, that channel must be bound to StreamStor via this command. XLRclearChannels must be called to unbind the channel(s) before calling XLRBindInputChannel.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *channel* is the channel number to bind – this is card specific.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Note: CHANGING MODES CLEARS ALL INPUT AND OUTPUT CHANNELS. CHANNELS MUST BE BOUND AFTER THE MODE IS SELECTED.

Usage:

```
SSHANDLE          xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
// Set StreamStor mode to Single Channel.
xlrReturnCode = XLRSetMode( xlrDevice, SS_MODE_SINGLE_CHANNEL );

xlrStatus = XLRclearChannels( xlrDevice );
// For input over the PCI bus, bind to channel zero.
xlrStatus = XLRBindInputChannel( xlrDevice, 0 );
if( xlrStatus != XLR_SUCCESS )
{
    return(1);
}
xlrStatus = XLRRecord( xlrDevice, 0, 1 );
if( xlrStatus != XLR_SUCCESS )
{
    return(1);
}
```

See Also:

XLRclearChannels, XLRBindOutputChannel, and XLRselectChannel.

XLRBindOutputChannel

Syntax:

```
XLR_RETURN_CODE XLRBindOutputChannel( SSHANDLE xlrDevice, UINT
channel )
```

Description:

XLRBindOutputChannel binds a channel for output FROM StreamStor. In other words, “output” is relative to StreamStor. To playback over a particular channel, that channel must be bound to StreamStor via this command. XLRClearChannels must be called to unbind the channel(s) before calling XLRBindOutputChannel.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *channel* is the channel number to bind – this is card specific.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Note: CHANGING MODES CLEARS ALL INPUT AND OUTPUT CHANNELS. CHANNELS MUST BE BOUND AFTER THE MODE IS SELECTED.

Usage:

```
SSHANDLE          xlrDevice;
S_READDESC        readDesc;

xlrStatus = XLROpen( 1, &xlrDevice );
xlrStatus = XLRClearChannels( xlrDevice );

// Set StreamStor mode to Single Channel.
xlrReturnCode = XLRSetMode( xlrDevice, SS_MODE_SINGLE_CHANNEL );

// Bind the channel for output from the StreamStor.
xlrStatus = XLRBindOutputChannel( xlrDevice, 0 );
if( xlrStatus != XLR_SUCCESS )
{
    return(1);
}
xlrStatus = XLRRead( xlrDevice, &readDesc );
if( xlrStatus != XLR_SUCCESS )
{
    return(1);
}
```

See Also:

`XLRClearChannels`, `XLREndInputChannel`, and `XLREndChannel`.

XLRCardReset

Syntax:

```
XLR_RETURN_CODE XLRCardReset( UINT index )
```

Description:

XLRCardReset will attempt to reset a StreamStor device and re-initialize the hardware and firmware. This function should be used only as a last resort.

Parameters:

- *index* is the card index number.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
xlrReturnCode = XLRCardReset( 1 );
```

See Also:

XLROpen and XLRReset.

XLRClearChannels

Syntax:

```
XLR_RETURN_CODE XLRClearChannels( SSHANDLE xlrDevice )
```

Description:

XLRClearChannels unbinds all input and output channels from StreamStor. The system cannot be reading or writing, and new input and output channels must be bound before any recording or playback operation is started. XLRClearChannels must be called before calling XLRBindInputChannel or XLRBindOutputChannel to unbind the channels.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device.
xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrStatus = XLRClearChannels( xlrDevice );
...
// Close device before exiting.
XLRclose( xlrDevice );
```

See Also:

XLRBindInputChannel, XLRBindOutputChannel, and XLRSelectChannel.

XLRClearWriteProtect

Syntax:

```
XLR_RETURN_CODE XLRClearWriteProtect( SSHANDLE xlrDevice )
```

Description:

`XLRClearWriteProtect` removes write protection from a previously write protected StreamStor recorder. By default, drives are not write protected. The drives must be idle (i.e., no recording or playback in progress) to clear the write protection.

If the StreamStor is in bank mode, this command will clear write protection only on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to `XLROpen`.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device.
xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrStatus = XLRClearWriteProtect( xlrDevice );
...
// Close device before exiting.
XLRclose( xlrDevice );
```

See Also:

`XLRSetWriteProtect`, `XLRSetBankMode` and `XLRSelectBank`.

XLRClose

Syntax:

```
void XLRClose( SSHANDLE xlrDevice )
```

Description:

XLRClose closes the StreamStor device. This should be called before exiting an application that has opened a StreamStor device with XLROpen. No other application can open the StreamStor device until this function has been called.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

None.

Usage:

```
SSHANDLE          xlrDevice;  
XLR_RETURN_CODE  xlrStatus;  
  
// Open the device  
xlrStatus = XLROpen( 1, &xlrDevice );  
.  
.  
.  
// Close device before exiting.  
XLRClose( xlrDevice );
```

See Also:

XLROpen.

XLRDeleteAppend

Syntax:

```
XLR_RETURN_CODE XLRDeleteAppend( SSHANDLE xlrDevice, ULONG  
AddrHigh, ULONG AddrLow )
```

Description:

XLRDeleteAppend deletes the last appended data set on the StreamStor device. An appended data set is defined as the data recorded to StreamStor with the XLRAppend function. An optional address can be provided to define the new last append start point. Zero should be used for the address in most circumstances.

The new last append address must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will delete appended data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *AddrHigh* is the upper 32 bits of the 64-bit address to use for the new last append start point. In most cases, this should be zero.
- *AddrLow* is the upper 32 bits of the 64-bit address to use for the new last append start point. In most cases, this should be zero.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device.
xlrStatus = XLROpen( 1, &xlrDevice );

// Append data.
xlrStatus = XLRAppend( xlrDevice );
.
.
.
// Stop recording.
XLRStop( xlrDevice );

// Delete just the data recorded above.
xlrStatus = XLRDeleteAppend( xlrDevice, 0, 0 );

// Close device before exiting
XLRClose( xlrDevice );
```

See Also:

XLRTruncate, XLRSetBankMode and XLRSelectBank.

XLRDeviceFind

Syntax:

```
UINT XLRDeviceFind( )
```

Description:

XLRDeviceFind searches the PCI bus(es) and returns the number of StreamStor cards present in the system.

Parameters:

None.

Return Value:

This function returns the number of StreamStor cards in the system. If the driver has not been installed properly, this function returns zero.

Usage:

```
UINT NumCards;  
  
if( NumCards = XLRDeviceFind() )  
{  
    // There are StreamStor cards on this system.  
    printf("StreamStor cards found: %d\n", NumCards );  
}  
else  
{  
    // No StreamStor cards on the system.  
    printf("No StreamStor cards detected!\n");  
}
```

See Also:

XLROpen.

XLRDismountBank

Syntax:

```
XLR_RETURN_CODE XLRDismountBank( SSHANDLE xlrDevice, UINT bankID
 )
```

Description:

XLRDismountBank will power down the selected bank. A bank can also be dismounted by a key on-off transition.

A dismounted bank can be re-powered by a key off-on transition or by calling XLRMountBank.

If you attempt to dismount a bank that has already been dismounted, no action is taken and XLR_SUCCESS is returned.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *bankID* is a constant indicating the bank to be dismounted (BANK_A or BANK_B).

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;
S_BANKSTATUS      AbankStatus;

// Open the device.
xlrStatus = XLROpen( 1, &xlrDevice );
xlrStatus = XLRSetBankMode ( xlrDevice, SS_BANKMODE_NORMAL );
xlrStatus = XLRGetBankStatus ( xlrDevice, BANK_A, &AbankStatus );
if ( AbankStatus.MediaStatus == MEDIASTATUS_FULL )
{
    printf ( "BANK A is full.\n" );
    xlrStatus = XLRDismountBank ( xlrDevice, BANK_A );
}
}
```

See Also:

XLRMountBank, XLRGetBankStatus, XLRSetBankMode and XLRSelectBank.

XLREdit

Syntax:

```
XLR_RETURN_CODE XLREdit(SSHANDLE xlrDevice, PS_READDESC
pReadDesc)
```

Description:

XLREdit edits data from the StreamStor device by overwriting existing data (specified by the AddrHi, AddrLo, and XferLength structure members of pReadDesc) with new data contained in the buffer pointed to by the BufferAddr structure member of pReadDesc.

The edit address of the requested data must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will edit the data on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pReadDesc* is a pointer to an S_READDESC structure that holds the edit address, length and buffer address containing the new data to overwrite the existing data.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrDevice;
S_READDESC    readDesc;
ULONG         myBuffer[40000];

xlrStatus = XLROpen( 1, &xlrDevice );
...
/* Fill buffer with new data here */

//AddrHi and AddrLo must represent an appropriately aligned address.
readDesc.AddrHi = 0;
readDesc.AddrLo = 0xFE120000;
readDesc.XferLength = sizeof( myBuffer );
readDesc.BufferAddr = myBuffer;

xlrReturnCode = XLREdit( xlrDevice, &readDesc );
```

See Also:

XLREditData, XLRSetBankMode and XLRSelectBank.

XLREditData

Syntax:

```
XLR_RETURN_CODE XLREditData( SSHANDLE xlrDevice,  
PULONG BufferAddr, ULONG AddrHigh, ULONG AddrLow,  
ULONG XferLength )
```

Description:

XLREditData edits data from the StreamStor device by overwriting existing data (specified by the *AddrHi*, *AddrLo*, and *XferLength* parameters) with new data contained in the buffer pointed to by the *BufferAddr*.

This function is identical to XLREdit without the structure to pass the edit parameters.

The edit address of the requested data must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will edit the data on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Buffer* is the address of the user memory buffer to hold the requested data.
- *AddrHigh* is the upper 32 bits of a 64-bit byte address of the requested data.
- *AddrLow* is the lower 32 bits of a 64-bit byte address of the requested data.
- *XferLength* is the number of bytes requested.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrDevice;  
XLR_RETURN_CODE  xlrReturnCode;  
ULONG         myBuffer[40000];
```

```
xlrReturnCode = XLROpen( 1, &xlrDevice );  
    ...
```

```
/* Fill buffer with new data here */
```

```
xlrReturnCode = XLREditData( xlrDevice, myBuffer, 0, 0xFE120000,  
sizeof(myBuffer) );
```

See Also:

XLREdit, XLRSetBankMode and XLRSelectBank.

XLRErase

Syntax:

```
XLR_RETURN_CODE XLRErase( SSHANDLE xlrDevice, SS_OWMODE mode )
```

Description:

XLRErase erases data on the drives.

If the StreamStor is in bank mode, this command will erase only the selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *mode* is the erase mode.

There are five erase modes:

- SS_OVERWRITE_NONE sets the directories to zero, such that the drives are reported as having no data. However, all data is still on the drives. XLRErase will return when this command is complete.
- SS_OVERWRITE_RANDOM_PATTERN overwrites all data on the drives with a random pattern so that the data is permanently deleted. XLRErase returns immediately, but the erasure can take several hours – use XLRGetDeviceStatus (see below) to find out when erasure is complete.
- SS_OVERWRITE_RW_PATTERN is similar to SS_OVERWRITE_RANDOM_PATTERN except that data is read first and then overwritten with a random pattern. This mode can be used to verify that all sectors can be read and written. Note that this mode will take on average twice as long as the SS_OVERWRITE_RANDOM_PATTERN mode to complete. XLRErase returns immediately, but the erasure can take several hours – use XLRGetDeviceStatus (see below) to find out when erasure is complete.
- SS_OVERWRITE_DIRECTORY destroys the directory locator block (for the currently selected partition, if the system is partitioned). This option will erase all data including the user directory and labels. Other partitions (if partitioned) are unaffected. XLRErase will return when this command is complete.
- SS_OVERWRITE_PARTITION destroys everything: all partitions, data, user directories, and labels. XLRErase will return when this command is complete.

As with other API functions that record data, XLRErase will immediately return control to the calling program. If an erase is in progress, XLRGetDeviceStatus will indicate that the device is in Recording mode.

If the SS_OVERWRITE_RANDOM_PATTERN mode is specified, and an overwrite operation is in progress, a call to XLRGetLength will return the number of bytes remaining to overwrite for the slowest bus. (Each bus is erased in parallel, thus it returns the number of bytes remaining for the slowest bus. In other words, when the slowest bus completes, the entire operation will be complete.)

If the `SS_OVERWRITE_RW_PATTERN` mode is specified, the erase is done in two passes. The first pass will read all blocks on the device and the second pass will write all blocks on the device. During the read pass, a call to `XLRGetLength` will return the number of bytes remaining to be read. During the write pass, a call to `XLRGetLength` will return the number of bytes remaining to be overwritten.

Stopping `StreamStor` part way through an overwrite erase will immediately set the directory length to zero. Restarting the overwrite erase will start from the beginning – not where you previously stopped.

The following table summarized what, in addition to the data, is erased.

Erase Option	Label Erased?	User directory Erased?	Partitions Removed?
<code>NONE</code>	No	No	No
<code>RANDOM_PATTERN</code>	No	No	No
<code>RW_PATTERN</code>	No	No	No
<code>DIRECTORY</code>	Yes	Yes	No
<code>PARTITION</code>	Yes	Yes	Yes

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```

SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrReturn;
DWORDLONG         xlrLength;

xlrReturn = XLROpen( 1, &xlrDevice );
if( xlrReturn != XLR_SUCCESS )
    return(1);
xlrReturn = XLERase( xlrDevice, SS_OVERWRITE_RANDOM_PATTERN );
if( xlrReturn != XLR_SUCCESS )
{
    return(1);
}

//
//Overwrite Erase Examples:
//Example 1: 2 20GB drives per bus - master / slave configuration
//
xlrLength = XLRGetLength( xlrDevice );
//xlrLength equals approximately 40GB - if called
//at the beginning of the erase.

//Example 2: 1 100GB drive per bus - master only configuration.
xlrLength = XLRGetLength( xlrDevice );
//xlrLength equals approximately 100GB - if called
//at the beginning of the erase.

```

CHAPTER 2 : FUNCTION REFERENCE

See Also:

XLRsetLabel, XLRSetUserDir, XLRGetBankStatus, XLRGetLength,
XLRSetWriteProtect, XLRclearWriteProtect, XLRSetBankMode and
XLRselectBank.

XLRGetBankStatus

Syntax:

```
XLR_RETURN_CODE XLRGetBankStatus( SSHANDLE xlrDevice, UINT
bankID, PS_BANKSTATUS pBankStatus )
```

Description:

XLRGetBankStatus retrieves information from the StreamStor about the specified *bankID*. The StreamStor must be in bank mode to get the status of a bank. XLRGetBankStatus can be called when the StreamStor is not idle.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *bankID* is a constant indicating the bank to report on (BANK_A or BANK_B).
- *pBankStatus* is a pointer to an S_BANKSTATUS structure.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_BANKSTATUS      AbankStatus;
S_BANKSTATUS      BbankStatus
XLR_RETURN_CODE   xlrStatus;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

xlrStatus = XLRSetBankMode ( xlrDevice, SS_BANKMODE_NORMAL );
xlrStatus = XLRGetBankStatus ( xlrDevice, BANK_A, &AbankStatus );
xlrStatus = XLRGetBankStatus ( xlrDevice, BANK_B, &BbankStatus );
if ( AbankStatus.MediaStatus == MEDIASTATUS_FULL )
{
    printf ( "BANK A is full.\n" );
}
if ( BbankStatus.MediaStatus == MEDIASTATUS_FULL )
{
    printf ( "BANK B is full.\n" );
}
```

See Also:

XLRGetDeviceStatus, XLRSetBankMode and XLRSelectBank.

XLRGetBaseAddr

Syntax:

```
ULONG XLRGetBaseAddr( SSHANDLE xlrDevice )
```

Description:

XLRGetBaseAddr returns the physical address of the recording data window. This address can be used to program PCI hardware devices for direct card-to-card data transfer. The address returned from this function is NOT a valid user address.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

This function returns the physical PCI address as a 32 bit unsigned integer.

Usage:

```
ULONG          xlrAddress;
SSHANDLE       xlrDevice;
XLR_RETURN_CODE xlrStatus;

xlrStatus = XLROpen( 1, &xlrDevice );
if( xlrStatus != XLR_SUCCESS )
{
    // Error opening StreamStor.
}
else
{
    xlrAddress = XLRGetBaseAddr( xlrDevice );
}
```

XLRGetBaseRange

Syntax:

```
ULONG XLRGetBaseRange( SSHANDLE xlrDevice )
```

Description:

XLRGetBaseRange returns the size of the StreamStor device data window in bytes. This range of addresses is intended to be used by hardware transferring data that cannot be programmed to write with a non-incrementing address. Note that the address used to write to StreamStor does not effect the storage location of the data; StreamStor always stores data sequentially in the order it is written regardless of the address.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

This function returns the window size in bytes.

Usage:

```
ULONG          xlrAddress, xlrRange;
SSHANDLE       xlrDevice;
XLR_RETURN_CODE xlrStatus;

xlrStatus = XLROpen( 1, &xlrDevice );
if( xlrStatus != XLR_SUCCESS )
{
    // Error opening StreamStor.
}
else
{
    xlrAddress = XLRGetBaseAddr( xlrDevice );
    xlrRange = XLRGetBaseRange( xlrDevice );
}
// DMA Hardware may now be programmed to write to any address from
// xlrAddress to (xlrAddress + xlrRange).
```

XLRGetDBInfo

Syntax:

```
XLR_RETURN_CODE XLRDBInfo(SSHANDLE xlrDevice, PS_DBInfo pdbInfo)
```

Description:

XLRGetDBInfo retrieves information from the StreamStor daughter board. The drives must be idle (i.e., no recording or playback in progress) to get daughter board information.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pdbInfo* is a pointer to an S_DBInfo structure.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_DBINFO          dbInfo;
XLR_RETURN_CODE   xlrStatus;

// Open the device.
xlrStatus = XLROpen( 1, &xlrDevice );

xlrStatus = XLRGetDBInfo( xlrDevice, &dbInfo );
printf( "Daughter board type is %s\n", dbInfo.PCBType );
```

See Also:

XLRGetDeviceInfo.

XLRGetChassisType

Syntax:

```
UINT XLRGetChassisType( SSHANDLE xlrDevice )
```

Description:

XLRGetChassisType retrieves an integer value representing the chassis type. The defined values for chassis types are:

- TK200 – a chassis that can hold two drive modules and supports bank switching.
- UNKNOWN_CHASSIS_TYPE – any chassis that is not a TK200 and therefore does not support bank switching.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

The chassis type, as described above.

Usage:

```
SSHANDLE      xlrDevice;
UINT          chassisType
XLR_RETURN_CODE xlrStatus;

xlrStatus = XLROpen(1, &xlrDevice);
chassisType = XLRGetChassisType(xlrDevice);
if (chassisType == TK200)
{
    printf ("This system supports bank switching.\n");
    xlrStatus = XLRSetBankMode(xlrDevice, SS_BANKMODE_NORMAL);
    xlrStatus = XLRSelectBank(xlrDevice, BANK_B);
    ...
}
else
{
    printf ("This system does not support bank switching.\n");
}
...
// Close device before exiting
XLRclose( xlrDevice );
```

See Also:

XLRSetBankMode and XLRSelectBank.

XLRGetDeviceInfo

Syntax:

```
XLR_RETURN_CODE XLRGetDeviceInfo( SSHANDLE xlrDevice, PS_DEVINFO
pDevInfo )
```

Description:

XLRGetDeviceInfo retrieves information from the StreamStor device about its physical configuration.

If the StreamStor is in bank mode, this command will report on the currently selected bank. For example, the number of drives reported will be the number of drives on the selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pDevInfo* is a pointer to an S_DEVINFO structure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_DEVINFO         devInfo;
XLR_RETURN_CODE   xlrReturn;

xlrReturn = XLROpen( 1, &xlrDevice );
if( xlrReturn != XLR_SUCCESS )
    return(1);
xlrReturn = XLRGetDeviceInfo( xlrDevice, &devInfo );
if( xlrReturn != XLR_SUCCESS )
    return(1);
printf("StreamStor serial number is: %d", devInfo.SerialNum );
```

See Also:

XLRGetDBInfo, XLRSetBankMode and XLRSelectBank.

XLRGetDeviceStatus

Syntax:

```
XLR_RETURN_CODE XLRGetDeviceStatus( SSHANDLE xlrDevice,
PS_DEVSTATUS pDevStatus )
```

Description:

XLRGetDeviceStatus retrieves status of the StreamStor device.

If the StreamStor is in bank mode, this command will report the device status of the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pDevStatus* is a pointer to an S_DEVSTATUS structure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_DEVSTATUS       devStatus;
XLR_RETURN_CODE   xlrReturn;

xlrReturn = XLROpen( 1, &xlrDevice );
if( xlrReturn != XLR_SUCCESS )
    return(1);
xlrReturn = XLRGetDeviceStatus( xlrDevice, &devStatus );
if( xlrReturn != XLR_SUCCESS )
    return(1);
if( devStatus.Recording )
    printf("StreamStor is recording.");
else
    printf("StreamStor is idle");
```

See Also:

XLRGetBankStatus, XLRSetBankMode and XLRSelectBank.

XLRGetDirectory

Syntax:

```
XLR_RETURN_CODE XLRGetDirectory( SSHANDLE xlrDevice, PS_DIR pDir
 )
```

Description:

XLRGetDirectory gets the directory information of the current recording on a StreamStor device. The drives must be idle (i.e., no recording or playback in progress) when this function is called.

If the StreamStor is in bank mode, this command will report directory information on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pDir* is a pointer to an S_DIR structure to be filled by this function call.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrReturn;
S_DIR             xlrDir;

xlrStatus = XLROpen( 1, &xlrDevice );

... Record some data ...

XLRStop(xlrDevice);
xlrReturn = XLRGetDirectory( xlrDevice, &xlrDir );
if( xlrReturn != XLR_SUCCESS )
{
    return(1);
}
```

See Also:

XLRGetLength, XLRGetBankStatus, XLRSetBankMode and XLRSelectBank.

XLRGetDriveInfo

Syntax:

```
XLR_RETURN_CODE XLRGetDriveInfo( SSHANDLE xlrDevice, UINT Bus,
  UINT MasterSlave, PS_DRIVEINFO pDriveInfo )
```

Description:

XLRGetDriveInfo retrieves info from the StreamStor drive about its physical configuration.

If the StreamStor is in bank mode, this command will get drive information for the drives in the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Bus* is the ATA bus number of the drive.
- *MasterSlave* is XLR_MASTER_DRIVE (0) or XLR_SLAVE_DRIVE (1) to select the master or slave drive on the ATA bus.
- *pDriveInfo* is a pointer to an S_DRIVEINFO structure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
S_DRIVEINFO       drvInfo;
XLR_RETURN_CODE   xlrReturn;

xlrReturn = XLROpen( 1, &xlrDevice );
if( xlrReturn != XLR_SUCCESS )
    return(1);
xlrReturn = XLRGetDriveInfo( xlrDevice, 0, XLR_MASTER_DRIVE, &drvInfo
);
if( xlrReturn != XLR_SUCCESS )
    return(1);
printf( "Drive serial number is: %s\n", drvInfo.Serial );
printf( "Drive model number is: %s\n", drvInfo.Model );
printf( "Drive revision: %s\n", drvInfo.Revision );
printf( "Drive capacity (sectors): %d\n", drvInfo.Capacity );
```

See Also:

XLRSetBankMode and XLRSelectBank.

XLRGetErrorMessage

Syntax:

```
XLR_RETURN_CODE XLRGetErrorMessage(char *string, XLR_ERROR_CODE
err)
```

Description:

XLRGetErrorMessage returns the error message of the most recent API failure.

Parameters:

- *string* is a pointer to a string to accept the error message of at least XLR_ERROR_LENGTH size.
- *err* is an error code returned from XLRGetLastError.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrHandle;
S_DIR             xlrDir;
XLR_RETURN_CODE   xlrReturn;
XLR_ERROR_CODE    xlrError;
char              temp[XLR_ERROR_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturn = XLRGetDirectory( xlrHandle, &xlrDir );
if( xlrReturn != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( temp, xlrError );
    printf( "Error message: %s\n", temp );
    exit(1);
}
```

See Also:

XLRGetLastError.

XLRGetEvents

Syntax:

```
XLR_RETURN_CODE XLRGetEvents ( IN SSHANDLE xlrDevice,  
    IN UINT bufSize, OUT PS_EVENTS events );
```

Description:

`XLRGetEvents` retrieves events that were captured as a result of setting one or more event options when calling the `XLRSetDBMode` function. (I.e., calling `XLRSetDBMode` with *option* set to `SS_OPT_EVENTLOG` bit-wise inclusively or'ed with an `SS_OPT_EVENT_*` option.)

Parameters:

- *xlrDevice* is the device handle returned from a previous call to `XLROpen`.
- *bufsize* is the size, in bytes, of *events*.
- *events* is a pointer to the buffer that is to receive the events.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
SSHANDLE      xlrHandle;
XLR_RETURN_CODE  xlrReturn;
UINT          eventCount=0;
UINT          idx;
PS_EVENTS     eventBufPtr = NULL;

xlrStatus = XLROpen( 1, &xlrDevice );

    // Select the desired channels....

//
// Set the FPDP mode and select the type of event to
// capture.  This shows how to capture events on
// rising edge of SYNC* signal on a PCI-816XF2.  Note that
// to use any of the SS_OPT_EVENT_* options, you must "or"
// the option (or options) with SS_OPT_EVENTLOG.
//
xlrStatus = XLRSetDBMode( xlrHandle,
    SS_FPDP_RECVMaster, SS_OPT_EVENTLOG | SS_OPT_EVENT_SYNC_RISE );

    // Record some data ...

xlrStatus = XLRStop( xlrHandle );

//
// Get the number of events that were captured so you know
// how much space to allocate to hold them.
//
eventCount = XLRGetEventsLength( xlrHandle );
eventBufPtr = (PS_EVENTS)malloc( eventCount * sizeof(S_EVENTS) );

//
// Retrieve the events into the array.
//
xlrStatus = XLRGetEvents( xlrHandle,
    eventCount * sizeof(S_EVENTS), eventBufPtr );

//
// Examine the events.
//
for ( idx = 0; idx < eventCount; idx++ )
{
    printf("Event[%u].Source = 0x%X - ", eventBufPtr[i].Source );
    printf( "Address: 0x%X%X\n",
        eventBufPtr[i].AddressHigh,
        eventBufPtr[i].AddressLow );
}
}
```

See Also:

XLRSelectChannel, XLRSetDBMode, XLRGetEventsLength.

XLRGetEventsLength

Syntax:

```
UINT XLRGetEventsLength( SSHANDLE xlrDevice )
```

Description:

XLRGetEventsLength returns the number of events that have been captured as a result of setting one or more event options when calling the XLRSetDBMode function. (I.e., calling XLRSetDBMode with *option* set to SS_OPT_EVENTLOG bit-wise inclusively or'ed with an SS_OPT_EVENT_* option.)

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

- The number of events that have been captured.

Usage:

```
SSHANDLE          xlrHandle;
UINT              numberOfEvents=0;
XLR_RETURN_CODE  xlrReturn;

xlrStatus = XLROpen( 1, &xlrDevice );

    // Capture events ...

numberOfEvents = XLRGetEventsLength( xlrHandle );
```

See Also:

XLRSelectChannel, XLRSetDBMode, and XLRGetEvents.

XLRGetFIFOLength

Syntax:

```
DWORDLONG XLRGetFIFOLength( SSHANDLE xlrDevice )
```

Description:

XLRGetFIFOLength returns the amount of data currently in the FIFO. This function is only valid when StreamStor is in a forking or pass thru mode (SS_MODE_FORK, SS_MODE_PASSTRHU). If StreamStor is not in one of the modes listed above, or is not currently moving data, XLRGetFIFOLength will return 0.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

Usage:

```
SSHANDLE          xlrDevice;
DWORDLONG         length = 0;

...

// Setup StreamStor in a valid fork or pass-thru mode

...
// Get the length of data in the fifo.
length = XLRGetFIFOLength( xlrDevice );
```

See Also:

XLRSetMode, XLRReadFIFO and XLRGetLength.

XLRGetLabel

Syntax:

```
XLR_RETURN_CODE XLRGetLabel( SSHANDLE xlrDevice, char *label )
```

Description:

XLRGetLabel returns the label on the StreamStor recorder where the label was previously set with the XLRSetLabel command. If no label has been previously set, a default label will be returned.

If the StreamStor is in bank mode, this command will return the label of the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *label* is a pointer to a string to accept a label of at least XLR_LABEL_LENGTH in size.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE  xlrStatus;
char              label[XLR_LABEL_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
xlrStatus = XLRSetLabel( xlrDevice, "Label 2" );
xlrStatus = XLRGetLabel( xlrDevice, label );
printf ( "This disk set is labeled %s\n", label );
...
// Null out the label.
label[0] = '\0';
XlrStatus = XLRSetLabel( xlrDevice, label );
...
// Close device before exiting
XLRclose( xlrDevice );
```

See Also:

XLRSetLabel, XLRerase, XLRSetBankMode and XLRSelectBank.

XLRGetLastError

Syntax:

```
XLR_ERROR_CODE XLRGetLastError( void )
```

Description:

XLRGetLastError returns the error code of the most recent API failure.

Parameters:

None.

Return Value:

This function returns the error code (see Appendix A).

Usage:

```
SSHANDLE          xlrDevice;
XLR_ERROR_CODE    xlrError;
char               errString[XLR_ERROR_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturn = XLRGetDirectory( xlrDevice, &xlrDir );
if( xlrReturn != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( errString, xlrError );
    printf( "Error message: %s\n", errString );
    exit(1);
}
```

See Also:

XLRGetErrorMessage.

XLRGetLength

Syntax:

```
DWORDLONG XLRGetLength( SSHANDLE xlrDevice )
```

Description:

XLRGetLength returns the length (in bytes) of the current recording as a 64-bit integer. This function can be used during an active recording or FIFO operation. Note that during active record and FIFO operations the returned value may not be exact since data is still moving between devices.

If the StreamStor is in bank mode, this command will return the length of the recording on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

- Current recording length in bytes.

Usage:

```
SSHANDLE          xlrHandle;  
DWORDLONG         recordingLength;  
XLR_RETURN_CODE  xlrReturnCode;
```

```
xlrReturnCode = XLROpen( 1, &xlrHandle );  
recordingLength = XLRGetLength( xlrHandle );
```

See Also:

XLRGetDirectory and XLRGetBankStatus.

XLRGetLengthLowHigh

Syntax:

```
void XLRGetLengthLowHigh( SSHANDLE xlrDevice, PULONG low, PULONG high )
```

Description:

XLRGetLengthLowHigh returns the current recording length (in bytes) in two 32-bit variables. This function is provided for programming environments unable to handle 64 bit integers.

If the StreamStor is in bank mode, the values returned will be for the recording on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *low* is a pointer to a ULONG (unsigned int) that will be written with the lower 32 bits of the recording size in bytes.
- *high* is a pointer to a ULONG (unsigned int) that will be written with the upper 32 bits of the recording size in bytes.

Return Value:

- None

See Also:

XLRSetBankMode and XLRSelectBank.

XLRGetLengthPages

Syntax:

```
ULONG XLRGetLengthPages( SSHANDLE xlrDevice )
```

Description:

XLRGetLengthPages returns the current recording length in units of system pages. This function is provided for programming environments unable to handle 64 bit integers. Windows environments typically utilize a page size of 4096 bytes but this should be checked using a query to the operating system.

If the StreamStor is in bank mode, the value returned will be for the recording on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

- Recording length in system pages.

See Also:

XLRSetBankMode and XLRSelectBank.

XLRGetMode

Syntax:

```
XLR_RETURN_CODE XLRGetMode( SSHANDLE xlrDevice, SSMODE pMode )
```

Description:

XLRGetMode returns the input/output path (or “port mode”) on the StreamStor recorder where the mode was previously set with the XLRSetMode command.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pmode* is a pointer to an SSMODE variable that will receive the mode.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrHandle;
XLR_RETURN_CODE   xlrStatus;
SSMODE            portMode;

xlrStatus = XLROpen( 1, &xlrDevice );
xlrStatus = XLRGetMode(xlrDevice, &portMode);

if( portMode == SS_MODE_SINGLE_CHANNEL )
{
    printf( "In single channel mode.\n" );
}
...
```

See Also:

XLRSetMode.

XLRGetPartitionInfo

Syntax:

```
XLR_RETURN_CODE XLRGetPartitionInfo( SSHANDLE xlrDevice,
PS_PARTITIONINFO pPartitionInfo )
```

Description:

XLRGetPartitionInfo retrieves information from the StreamStor about the currently selected partition.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pPartitionInfo* is a pointer to an S_PARTITIONINFO structure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrDevice;
S_PARTITIONINFO  partitionInfo;

// Open the device.
if( XLROpen( 1, &xlrDevice ) != XLR_SUCCESS )
{
    printf( "ERROR: Open failed: %u\n", XLRGetLastError() );
    exit( -1 );
}

if( XLRGetPartitionInfo( xlrDevice, &partitionInfo ) != XLR_SUCCESS )
{
    printf( "ERROR: GetPartitionInfo failed: %u\n", XLRGetLastError() );
    exit( -1 );
}

printf( "Number of partitions = %u\n", partitionInfo.NumPartitions);
```

See Also:

XLRPartitionCreate and XLRPartitionSelect.

XLRGetPlayLength

Syntax:

```
DWORDLONG XLRGetPlayLength( SSHANDLE xlrDevice )
```

Description:

XLRGetPlayLength returns the number of bytes that have been played back between calling XLRPlayback and XLRStop.

You can call XLRGetPlayLength while the StreamStor is playing back. In this case, however, the number of bytes played back is only an estimate (because the number of bytes played back is updated internally approximately every three seconds).

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

- Number of bytes played back. Zero is returned if an error occurred.

Usage:

```
SSHANDLE    xlrDevice;
ULONG       addrHi, addrLow;
DWORDLONG   bytesPlayed;
char        errorMessage[XLR_ERROR_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
...
addrHi = 0;
addrLow = 0xFE120000;

xlrReturnCode = XLRPlayback( xlrDevice, addrLow, addrHi );
...
XLRStop(xlrDevice);

// Get the number of bytes that were played back.
bytesPlayed = XLRGetPlayLength(xlrDevice);
if ( bytesPlayed == 0 ) {
    printf ( "Nothing got played back.\n" );
    XLRGetErrorMessage( errorMessage, XLRGetLastError() );
    printf( "XLRGetPlayLength error: %s\n", errorMessage );
}
```

See Also:

XLRPlayback and XLRSetPlaybackLength.

XLRGetSystemAddr

Syntax:

```
ULONG XLRGetSystemAddr( SSHANDLE xlrDevice )
```

Description:

XLRGetSystemAddr returns the kernel address of the recording data window. This address can be used from device drivers or other kernel level software. The address returned from this function is NOT a valid user address.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

This function returns the physical PCI address as a 32 bit unsigned integer.

Usage:

```
ULONG          xlrAddress;
SSHANDLE       xlrDevice;
XLR_RETURN_CODE xlrStatus;

xlrStatus = XLROpen( 1, &xlrDevice );
if( xlrStatus != XLR_SUCCESS )
{
    // Error opening StreamStor.
}
else
{
    xlrAddress = XLRGetSystemAddr( xlrDevice );
}
```

XLRGetUserDir

Syntax:

```
XLR_RETURN_CODE XLRGetUserDir( SSHANDLE xlrDevice, UINT
xferLength,
    UINT offset, PVOID udirPtr)
```

Description:

XLRGetUserDir returns the user directory on the StreamStor recorder where the user directory was previously set with the XLRSetUserDir command.

If the StreamStor is in bank mode, this command will return the user directory of the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *xferLength* is the length of the user directory. The maximum size of a user directory is XLR_MAX_UDIR_LENGTH.
- *offset* is the beginning offset into the user directory.
- *udirPtr* is a pointer to a buffer large enough to hold the expected user directory.

Note: This command can be very slow over the remote interface.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
ULONG          xlrAddress;
SSHANDLE       xlrDevice;
XLR_RETURN_CODE xlrStatus;
char          userDirBuff[1024];
UINT          dirLength;

xlrStatus = XLROpen( 1, &xlrDevice );
dirLength = XLRGetUserDirLength( xlrDevice );
if ( dirLength == 0 ) {
    printf ( "This system does not have a user directory.\n" );
}
else {
    xlrStatus = XLRGetUserDir ( xlrDevice, dirLength, 0, userDirBuff );
}

...
// Close device before exiting
XLRclose( xlrDevice );
```

See Also:

XLRSetUserDirectory, XLRGetUserDirLength, XLRSetBankMode and
XLRSelectBank.

XLRGetUserDirLength

Syntax:

```
UINT XLRGetUserDirLength( SSHANDLE xlrDevice )
```

Description:

XLRGetUserDirLength returns the length (in bytes) of the user directory on the StreamStor recorder where the user directory was previously set with the XLRSetUserDir command.

If the StreamStor is in bank mode, this command will return the length of the user directory on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

Length of the user directory.

Usage:

```
ULONG          xlrAddress;
SSHANDLE       xlrDevice;
XLR_RETURN_CODE xlrStatus;
char          userDirBuff[1024];
UINT          dirLength;
UINT          offset;
```

```
xlrStatus = XLROpen( 1, &xlrDevice );
dirLength = XLRGetUserDirLength( xlrDevice );
if ( dirLength == 0 )
{
    printf ( "This system does not have a user directory.\n" );
}
else
{
    offset = 0;
    xlrStatus = XLRGetUserDir( xlrDevice, dirLength, offset, userDirBuff );
}

...
// Close device before exiting.
XLRclose( xlrDevice );
```

See Also:

XLRSetUserDir, XLRGetUserDir, XLRSetBankMode and XLRSelectBank.

XLRGetVersion

Syntax:

```
XLR_RETURN_CODE XLRGetVersion( SSHANDLE xlrDevice, PS_XLRSWREV
pVersion )
```

Description:

XLRGetVersion gets the API and firmware version information from a StreamStor device.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pVersion* is a pointer to an S_XLRSWREV structure to hold the version strings returned.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;
S_XLRSWVER  swVersion;
char        temp[XLR_ERROR_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRGetVersion( xlrDevice, &swVersion );
if( xlrReturnCode != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( temp, xlrError );
    printf( "%s\n", temp );
    exit(1);
}
printf("Firmware version: %s\n", swVersion.FirmwareVersion );
```

See Also:

XLRApiVersion and XLRGetDBInfo.

XLRGetWindowAddr

Syntax:

```
PULONG XLRGetWindowAddr( SSHANDLE xlrDevice )
```

Description:

XLRGetWindowAddr returns the user virtual address of the recording data window. This address can be used to directly write data to the StreamStor device from a user program.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

This function returns a pointer to the data window mapped into the user virtual address space.

Usage:

```
PULONG          xlrAddress;
SSHANDLE        xlrDevice;
XLR_RETURN_CODE xlrReturn;

xlrReturn = XLROpen( 1, &xlrDevice );
if( xlrReturn == XLR_SUCCESS )
{
    xlrAddress = XLRGetWindowAddr( xlrDevice );
    *xlrAddress = someData;

    // SomeData has been written to the StreamStor device, note that
    // xlrAddress does not need to be incremented for subsequent writes.
}
```

XLRMountBank

Syntax:

```
XLR_RETURN_CODE XLRMountBank( SSHANDLE xlrDevice, UINT bankId )
```

Description:

XLRMountBank will power up the selected bank. A dismantled bank can also be re-powered by a key off-on transition.

A mounted bank can be powered off by a key on-off transition or by calling XLRDismountBank.

If you attempt to mount a bank that is already mounted, no action is taken and XLR_SUCCESS is returned.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *bankID* is a constant indicating the bank to be mounted (BANK_A or BANK_B).

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;
S_BANKSTATUS      AbankStatus;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

xlrStatus = XLRSetBankMode ( xlrDevice, SS_BANKMODE_NORMAL );
xlrStatus = XLRGetBankStatus ( xlrDevice, BANK_A, &AbankStatus );
if ( AbankStatus.MediaStatus == MEDIASTATUS_FULL )
{
    printf ( "BANK A is full.  Wait for bank to dismount\n" );
    printf ( "then insert new bank module into BANK A.\n" );
    xlrStatus = XLRDismountBank ( xlrDevice, BANK_A );
    ... wait for new bank to be inserted ...
    xlrStatus = XLRMountBank (xlrDevice, BANK_A);
}
}
```

See Also:

XLRDismountBank, XLRGetBankStatus, XLRSetBankMode and XLRSelectBank.

XLRNetOpen (Windows Only)

Syntax:

```
XLR_RETURN_CODE XLRNetOpen( UINT devIndex, const char *address,
USHORT port, SSHANDLE *pXlrHandle )
```

Description:

XLRNetOpen opens a remote StreamStor device over an Ethernet link and initializes the hardware and firmware in preparation for recording on an external interface. The device is transitioned to system ready state if required. This function must be called before any other API function if using an Ethernet interface to StreamStor. After successful completion of this function, the handle pointed to by *pXlrHandle* can be used for all subsequent API calls.

NOTE: You should call XLRClose even if XLRNetOpen returns XLR_FAIL.

Parameters:

- *devIndex* identifies the desired StreamStor to open when multiple StreamStor devices are in use. Use 1 for single card systems. This is a user defined index value.
- *address* is a pointer to an array with a valid IPv4 address in dotted-quad notation (xxx.xxx.xxx.xxx), i.e. ("127.0.0.1").
- *port* indicates which network port the connection to StreamStor should be made on (default is 10001).
- *pXlrHandle* is a pointer to a system handle for initialization. Successful completion loads this parameter with a valid handle to the hardware device to use in subsequent API calls. **pXlrHandle* is assigned the value INVALID_SSHANDLE on failure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrHandle;
XLR_RETURN_CODE  xlrReturnCode;
ULONG         xlrError;
char          errString[XLR_ERROR_LENGTH];

if( XLRNetOpen( 1, "127.0.0.1", 10001, &xlrHandle ) != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( errString, xlrError );
    printf( "%s\n", errString );
    XLRclose( xlrHandle );
    exit(1);
}
.
.
.
XLRclose( xlrHandle );
```

See Also:

XLRclose.

XLROpen

Syntax:

```
XLR_RETURN_CODE XLROpen( UINT devIndex, SSHANDLE *pXlrHandle )
```

Description:

XLROpen opens a StreamStor device and initializes the hardware and firmware in preparation for recording. The device is transitioned to system ready state if required. This function must be called before any other API function. After successful completion of this function, the handle pointed to by *pXlrHandle* can be used for all subsequent API calls.

NOTE: You should call XLRClose even if XLROpen returns XLR_FAIL.

Parameters:

- *devIndex* identifies the desired StreamStor to open when multiple StreamStor devices are in use. Use 1 for single card systems. Use XLRDeviceFind to find the number of devices installed.
- *pXlrHandle* is a pointer to a system handle for initialization. Successful completion loads this parameter with a valid handle to the hardware device to use in subsequent API calls. **pXlrHandle* is assigned the value INVALID_SSHANDLE on failure.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrHandle;
XLR_RETURN_CODE   xlrReturnCode;
ULONG             xlrError;
char              errString[XLR_ERROR_LENGTH];

xlrReturnCode = XLROpen( 1, &xlrHandle );
if( xlrReturnCode != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( errString, xlrError );
    printf( "%s\n", errString );
    XLRclose( xlrHandle );
    exit(1);
}
.
.
.
XLRclose( xlrHandle );
```

See Also:

XLRclose, XLRDeviceFind, XLRSetBankMode, and XLRSelectBank.

XLRPartitionCreate

Syntax:

```
XLR_RETURN_CODE XLRPartitionCreate( SSHANDLE xlrDevice, DWORDLONG
length )
```

Description:

XLRPartitionCreate will create a new partition following any previously created partitions. A maximum of XLR_MAX_PARTITIONS partitions are allowed.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *length* is the size in bytes of the partition to create.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE xlrDevice;

if( XLROpen( 1, &xlrDevice ) != XLR_SUCCESS )
{
    printf( "Error: Open failed: %u\n", XLRGetLastError() );
    exit( -1 );
}

if( XLRPartitionCreate( xlrDevice, 0x10000000 ) != XLR_SUCCESS )
{
    printf( "Error: PartitionCreate failed: %u\n", XLRGetLastError() );
    exit( -1 );
}
```

See Also:

XLRPartitionSelect and XLRGetPartitionInfo.

XLRPartitionSelect

Syntax:

```
XLR_RETURN_CODE XLRPartitionSelect( SSHANDLE xlrDevice, ULONG
partition )
```

Description:

XLRPartitionSelect will select an already existing partition. Partitions are numbered starting at 0. Thus, a 5 partition system will contain partitions: 0, 1, 2, 3, and 4.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *partition* is the partition number to select.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE xlrDevice;

if( XLROpen( 1, &xlrDevice ) != XLR_SUCCESS )
{
    printf( "Error: Open failed: %u\n", XLRGetLastError() );
    exit( -1 );
}

if( XLRPartitionSelect( xlrDevice, 4 ) != XLR_SUCCESS )
{
    printf( "Error: PartitionSelect failed: %u\n", XLRGetLastError() );
    exit( -1 );
}
```

See Also:

XLRPartitionCreate and XLRGetPartitionInfo.

XLRPlayback

Syntax:

```
XLR_RETURN_CODE XLRPlayback( SSHANDLE xlrDevice, ULONG Addrhigh,  
ULONG AddrLow )
```

Description:

XLRPlayback puts StreamStor into playback mode where data is made available for transfer to an outside device. The supplied address will be used to set the starting point of the data to be made available for transfer.

Playback continues until:

- XLRStop is called to halt the playback or
- all data is played back or
- a play limit (see XLRSetPlaybackLength) is reached.

This function can be used for streaming data out the external (FPDP) port or it can be used in conjunction with XLRSetReadLimit to allow a PCI device to source data from StreamStor.

The playback address must be an eight-byte aligned value.

If the StreamStor is in bank mode, this command will play back data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *AddrHigh* is the upper 32-bit value of the 64-bit address to begin reading.
- *AddrLow* is the lower 32-bit value of the 64-bit address to begin reading.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
// This example shows how you can stream data out the external
// (FPDP) port.

#include <stdio.h>
#include <stdlib.h>
#include "xlrapi.h"

int main( int argc, char *argv[] )
{
    SSHANDLE          xlrDevice;
    S_DEVINFO         devInfo;
    DWORDLONG         bytesPlayed;
    DWORDLONG         offset;
    DWORDLONG         recordingLength;
    ULONG             AddrHi;
    ULONG             AddrLo;
    XLR_RETURN_CODE   xlrStatus;
    char              errorMessage[XLR_ERROR_LENGTH];

    xlrStatus = XLROpen( 1, &xlrDevice );
    if( xlrStatus != XLR_SUCCESS )
    {
        XLRGetErrorMessage( errorMessage, XLRGetLastError() );
        printf( "Error opening device: %s\n", errorMessage );
        exit(1);
    }

    xlrStatus = XLRGetDeviceInfo( xlrDevice, &devInfo );
    if( xlrStatus != XLR_SUCCESS )
    {
        XLRGetErrorMessage( errorMessage, XLRGetLastError() );
        printf( "Error getting device information: %s\n", errorMessage );
        XLRclose( xlrDevice );
        exit(1);
    }

    // Use the external port for playback.
    xlrStatus = XLRSetMode( xlrDevice, SS_MODE_SINGLE_CHANNEL );
    if( xlrStatus != XLR_SUCCESS )
    {
        XLRGetErrorMessage( errorMessage, XLRGetLastError() );
        printf( "Error setting the mode: %s\n", errorMessage );
        XLRclose( xlrDevice );
        exit(1);
    }

    xlrStatus = XLRBindInputChannel( xlrDevice, 0 );
    if( xlrStatus != XLR_SUCCESS )
    {
        XLRGetErrorMessage( errorMessage, XLRGetLastError() );
        printf( "Error setting the mode: %s\n", errorMessage );
        XLRclose( xlrDevice );
        exit(1);
    }
}
```

CHAPTER 2 : FUNCTION REFERENCE

```
xlrStatus = XLRBindOutputChannel( xlrDevice, 0 );
if( xlrStatus != XLR_SUCCESS )
{
    XLRGetErrorMessage( errMessage, XLRGetLastError() );
    printf( "Error setting the mode: %s\n", errMessage );
    XLRclose( xlrDevice );
    exit(1);
}

recordingLength = XLRGetLength( xlrDevice);
if ( recordingLength == 0 )
{
    printf ( "No data to playback.\n" );
    XLRclose( xlrDevice );
    exit(0);
}
// Set the FPDP mode.  SS_FPDP_XMIT does not drive the clock.
xlrStatus = XLRSetDBMode( xlrDevice,SS_FPDP_XMIT,0 );
if ( xlrStatus != XLR_SUCCESS )
{
    XLRGetErrorMessage( errMessage, XLRGetLastError() );
    printf( "Error setting FPDP mode: %s\n", errMessage );
    XLRclose( xlrDevice );
    exit(1);
}

// An offset of zero starts playback at the beginning.
offset= 0;

AddrHi = offset >> 32;
AddrLo = offset & 0xFFFFFFFF;

// Start the playback.
xlrStatus = XLRplayback(xlrDevice, AddrHi, AddrLo);
if (xlrStatus != XLR_SUCCESS)
{
    XLRGetErrorMessage( errMessage, XLRGetLastError() );
    printf( "Error with playback: %s\n", errMessage );
    XLRclose( xlrDevice );
    exit(1);
}

... Sleep, allowing playback to continue...

// Stop playback.
XLRStop (xlrDevice);

bytesPlayed = XLRGetPlayLength(xlrDevice);
printf ("Number of bytes played = %llu\n", bytesPlayed);

XLRclose(xlrDevice);
}
```

CHAPTER 2 : FUNCTION REFERENCE

See Also:

XLRStop, XLRRead, XLRSetPlaybackLength, XLRGetPlayLength,
XLRSetMode, XLRSetDBMode, XLRSetBankMode and XLRSelectBank.

XLRRead

Syntax:

```
XLR_RETURN_CODE XLRRead(SSHANDLE xlrDevice, PS_READDESC
pReadDesc)
```

Description:

XLRRead reads data from the StreamStor device.

The address of the requested data must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will read data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pReadDesc* is a pointer to an S_READDESC structure that holds the read address, length and buffer address for the read data.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrDevice;
S_READDESC    readDesc;
ULONG         myBuffer[40000];

xlrStatus = XLROpen( 1, &xlrDevice );
...
//AddrHi and AddrLo must represent an appropriately aligned address.
readDesc.AddrHi = 0;
readDesc.AddrLo = 0xFE120000;
readDesc.XferLength = sizeof( myBuffer );
readDesc.BufferAddr = myBuffer;

xlrReturnCode = XLRRead( xlrDevice, &readDesc );
```

See Also:

XLRPlayback, XLRSetMode, XLRSetDBMode, XLRSetBankMode and XLRSelectBank.

XLRReadData

Syntax:

```
XLR_RETURN_CODE XLRReadData( SSHANDLE xlrDevice, PULONG Buffer,
ULONG AddrHigh, ULONG AddrLow, ULONG XferLength )
```

Description:

XLRReadData reads data from the StreamStor device. This function is identical to XLRRead without the structure to pass request parameters.

The address of the requested data must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will read data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Buffer* is the address of the user memory buffer to hold the requested data.
- *AddrHigh* is the upper 32 bits of a 64-bit byte address of the requested data.
- *AddrLow* is the lower 32 bits of a 64-bit byte address of the requested data.
- *XferLength* is the number of bytes requested.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE  xlrReturnCode;
ULONG            myBuffer[40000];

xlrReturnCode = XLROpen( 1, &xlrDevice );
...
//AddrHigh and AddrLow must represent an appropriately aligned address.
xlrReturnCode = XLRReadData( xlrDevice, myBuffer, 0, 0xFE120000,
sizeof(myBuffer) );
```

See Also:

XLRRead, XLRSetMode, XLRSetDBMode, XLRSetBankMode and XLRSelectBank.

XLRReadFifo

Syntax:

```
XLR_RETURN_CODE XLRReadFifo( SSHANDLE xlrDevice, PULONG Buffer,
ULONG Length, BOOLEAN Direct )
```

Description:

XLRReadFifo reads data from the StreamStor device during a FIFO operation. Data can continue to be read with this function until the FIFO is empty or XLRStop is called. Note that the device must be in record mode when XLRReadFifo is called.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Buffer* is the address of the buffer to receive the read data.
- *Length* is the length of data to transfer in bytes.
- *Direct* is a flag that indicates if the supplied *Buffer* address is a physical address for direct transfer. For normal transfer to a user memory buffer this flag should be FALSE (0).

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;
ULONG       myBuffer[40000];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRReadFifo(xlrDevice, myBuffer, sizeof(myBuffer),
FALSE);
```

See Also:

XLRGetFifoLength, XLRRecord, XLRSetDBMode, XLRSetBankMode and XLRSelectBank.

XLRReadImmed

Syntax:

```
XLR_RETURN_CODE XLRReadImmed( SSHANDLE xlrDevice, PS_READDESC  
pReadDesc )
```

Description:

XLRReadImmed reads data from the StreamStor device without waiting for completion. You must receive XLR_READ_COMPLETE status from XLRReadStatus before any other commands can be issued. Note that only a single outstanding request is allowed per execution thread.

The address of the requested data must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will read data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pReadDesc* is a pointer to an S_READDESC structure that holds the read address, length and buffer address for the read data.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

CHAPTER 2 : FUNCTION REFERENCE

Usage:

```
SSHANDLE      xlrDevice;
S_READDESC   readDesc;
ULONG        myBuffer[40000];
XLR_READ_STATUS readStatus;
XLR_RETURN_CODE xlrReturnCode;

xlrStatus = XLROpen( 1, &xlrDevice );
...

//AddrHi and AddrLo must represent an appropriately aligned address.
readDesc.AddrHi = 0;
readDesc.AddrLo = 0xFE120000;
readDesc.XferLength = sizeof( myBuffer );
readDesc.BufferAddr = myBuffer;

xlrReturnCode = XLRReadImmed( xlrDevice, &readDesc );

/* DO SOME NON-STREAMSTOR RELATED WORK HERE */

readStatus = XLRReadStatus( TRUE );
if( readStatus != XLR_READ_COMPLETE )
{
    /* PROCESS ERROR! */
}
```

See Also:

XLRReadStatus, XLRSetBankMode and XLRSelectBank.

XLRReadStatus

Syntax:

```
XLR_RETURN_CODE XLRReadStatus( BOOLEAN Wait )
```

Description:

XLRReadStatus checks status of a read request issued with XLRReadImmed data from the StreamStor device.

If the StreamStor is in bank mode, this command will check the status of the currently selected bank.

Parameters:

- *Wait* is a flag to indicate whether to wait for completion of the read request. If TRUE, the function will not return until the read is complete or an error has occurred.

Return Value:

If the read request has completed: XLR_READ_COMPLETE

If the read request is waiting to execute: XLR_READ_WAITING

If the read request is currently executing: XLR_READ_RUNNING

If an error occurred during execution of the request: XLR_READ_ERROR

Usage:

```
SSHANDLE          xlrDevice;
S_READDESC        readDesc;
ULONG             myBuffer[40000];
XLR_READ_STATUS   readStatus;
XLR_RETURN_CODE   xlrReturnCode;

xlrStatus = XLROpen( 1, &xlrDevice );
...
readDesc.AddrHi = 0;
readDesc.AddrLo = 0xFE120000;
readDesc.XferLength = sizeof( myBuffer );
readDesc.BufferAddr = myBuffer;

xlrReturnCode = XLRReadImmed( xlrDevice, &readDesc );

while( moreWork )
{
    /* DO OTHER WORK HERE */
    readStatus = XLRReadStatus( FALSE );
    if( readStatus == XLR_READ_ERROR )
    {
        /* PROCESS ERROR! */
    }
    else if( readStatus == XLR_READ_COMPLETE )
        break;
}
```

CHAPTER 2 : FUNCTION REFERENCE

See Also:

XLRReadImmed, XLRSetBankMode and XLRSelectBank.

XLRReadToPhy

Syntax:

```
XLR_RETURN_CODE XLRReadToPhy( SSHANDLE xlrDevice, PS_READDESC


pReadDesc )


```

Description:

XLRReadToPhy reads data from the StreamStor device and writes directly to a supplied physical hardware address. This function is intended only for moving data between StreamStor and another device on the bus. The buffer address supplied MUST be a physical address and the entire transfer size must be available. The supplied address and length will be used to directly program the StreamStor DMA to transfer the data. Specifying incorrect addresses to this function can cause system crashes and instability.

The address of the requested data must be an eight byte-aligned value.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pReadDesc* is a pointer to an S_READDESC structure that holds the read address, length and physical address for the read data.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;
S_READDESC  readDesc;

xlrStatus = XLROpen( 1, &xlrDevice );
...
//AddrHi and AddrLo must represent an appropriately aligned address.
readDesc.AddrHi = 0;
readDesc.AddrLo = 0xFE120000;
readDesc.XferLength = XLRGetBaseRange( xlrDevice );
readDesc.BufferAddr = myDeviceAddress;

xlrReturnCode = XLRReadToPhy( xlrDevice, &readDesc );
```

See Also:

XLRPlayback.

XLRRecord

Syntax:

```
XLR_RETURN_CODE XLRRecord( SSHANDLE xlrDevice, BOOLEAN
WrapEnable, SHORT ZoneRange )
```

Description:

XLRRecord starts the record mode of the StreamStor device. After a successful call of this function, the StreamStor device will record to disk any data written to its data window on PCI or to its external data port. Recording will continue until the device is full or until XLRStop is called (whichever occurs first.)

If the StreamStor is in bank mode, this command will record on the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *WrapEnable* should be set to 1 to allow StreamStor to operate as a circular buffer. The oldest data will be overwritten if more data is received than is available on the disk drives. To force StreamStor to stop accepting data at the disk storage limits, set this parameter to 0.
- *ZoneRange* is not currently supported and should be set to 1.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...

// Start recording data but ensure that no captured data is
// overwritten.
xlrReturnCode = XLRRecord( xlrDevice, 0, 1 );

/* System is now recording . . . */

// End the recording.
XLRStop(xlrDevice);
```

See Also:

XLRAppend, XLRWrite, XLRStop, XLRSetBankMode and XLRSelectBank.

XLRRecoverData

Syntax:

```
XLR_RETURN_CODE XLRRecoverData( SSHANDLE xlrDevice, IN UINT Mode
)
```

Description:

XLRRecoverData attempts to recover data.

If partitioning was used on the system, prior to calling XLRRecoverData, you should call XLRPartitionSelect to select the partition that was in use prior to the failure (or prior to the overwrite).

XLRRecoverData does not recover the user directory or label - it will only attempt to recover the main data area. The last partial block of data may be truncated upon recovery, so you may lose up to 64K bytes of data.

Note that in some cases, no recovery or only partial recovery of data is possible. It is the user's responsibility to verify the integrity of any recovered data and, if necessary, truncate any corrupted data from the recording.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Mode* is the type of recovery that is to be performed.
 - If a recording has ended without calling XLRStop (as might happen if the StreamStor's power fails), StreamStor's directory may be corrupted. To recover data in this case, set *Mode* to SS_RECOVER_POWERFAIL.
 - If a recording has been partially overwritten, the data that has not been overwritten may be recoverable. To recover data in this case, set *Mode* to SS_RECOVER_OVERWRITE.
 - If a recording has been accidentally erased, but not overwritten, the data may still be recoverable. To recover data in this case, set *Mode* to SS_RECOVER_UNERASE.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...

// Attempt to repair StreamStor directory and recover data.
xlrReturnCode = XLRRecoverData( xlrDevice, SS_RECOVER_POWERFAIL );
```

See Also:

XLRPartitionSelect.

XLRReset

Syntax:

```
XLR_RETURN_CODE XLRReset( SSHANDLE xlrDevice )
```

Description:

XLRReset will attempt to reset a StreamStor device and re-initialize the hardware and firmware. This function should be used only as a last resort.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;  
  
xlrStatus = XLROpen( 1, &xlrDevice );  
...  
xlrReturnCode = XLRReset( xlrDevice );
```

See Also:

XLRCardReset.

XLRRetrieveEvents

Syntax:

```
XLR_RETURN_CODE XLRRetrieveEvents( SSHANDLE xlrDevice, DWORDLONG
EventLog[] )
```

Description:

XLRRetrieveEvents downloads an array of 64 bit integers into the EventLog[] array. Each integer is an offset into the current recording. An “event” is recorded for each FPD *SYNC pulse if the SS_OPT_FPDPEVENTLOG option is set in XLRSetDBMode. A maximum of MAX_EVENTS events can be captured. Positions in the EventLog array that do not contain an event are set to 0.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *EventLog[]* is an array of 64 bit integers.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrReturnCode;
DWORDLONG         Events[MAX_EVENTS];
UINT              i;

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRRetrieveEvents( xlrDevice, Events );
if( xlrReturnCode != XLR_SUCCESS )
{
    printf("ERROR\n");
    return 1;
}

for( i = 0; i < MAX_EVENTS; i++ )
{
    if( Events[i] == 0 )
    {
        // No more events recorded.
        break;
    }
    printf("Event %d: %ull\n", i, Events[i]);
}
```

See Also:

`XLSetDBMode`.

XLRSelectBank

Syntax:

```
XLR_RETURN_CODE XLRSelectBank( SSHANDLE xlrDevice, UINT bankID )
```

Description:

XLRSelectBank will select the specified bank. Subsequent calls to bank aware commands will then perform their operations on the selected bank. For example, if BANK_B is the currently selected bank, then a subsequent call to XLRSetLabel will label BANK_B.

Once a bank is selected, that bank remains selected until the other bank is explicitly selected or the StreamStor mode is changed. For example, say BANK_B was selected, a record was performed, and then XLRClose was called. Upon reopening the StreamStor with XLROpen, unless XLRSetBankMode was called to take the system out of bank mode or the select bank was changed with XLRSelectBank, the system would still be in bank mode and BANK_B would be the selected bank.

The StreamStor must be in bank mode to select a bank. When calling XLRSelectBank, the drive module to be selected must be mounted in the selected bank and be in the “ready” state.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *bankID* is the bank to be selected (BANK_A or BANK_B).

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

xlrStatus = XLRSetBankMode ( xlrDevice, SS_BANKMODE_NORMAL );

// Clear the write protection on Bank A.
xlrStatus = XLRSelectBank ( xlrDevice, BANK_A );
xlrStatus = XLRClearWriteProtect( xlrDevice );
// Set the write protection on Bank B.
xlrStatus = XLRSelectBank ( xlrDevice, BANK_B );
xlrStatus = XLRSetWriteProtect( xlrDevice );
```

See Also:

XLRSetBankMode and XLRGetBankStatus.

XLRSelectChannel

Syntax:

```
XLR_RETURN_CODE XLRSelectChannel(SSHANDLE xlrDevice, UINT
channel)
```

Description:

XLRSelectChannel selects the channel that future commands will operate on. A channel can be selected and operated on regardless of whether or not it's bound.

Channel number 0 is for PCI mode. Channel numbers 30 and 31 are for FPDP mode. Channel 30 is the channel number of the Top FPDP connector and channel number 31 is the Front FPDP connector.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *channel* is the number of the channel to select.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...

xlrStatus = XLRSelectChannel( xlrDevice, 30 );
...

xlrStatus = XLRSetDBMode( xlrDevice, SS_FPDP_RECVMaster, 0 );
...
```

See Also:

XLRClearChannels, XLRBindInputChannel, and XLRSetDBMode.

XLRSelfTest

Syntax:

```
XLR_RETURN_CODE XLRSelfTest( SSHANDLE xlrDevice, SS_SELFTEST test
)
```

Description:

XLRSelfTest performs an internal self-test on the StreamStor device. **After self testing has completed, you should reset the StreamStor card.**

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *test* is a constant specifying what kind of test you wish to perform. Possible values are:
 - XLR_BIST_PCI – test communications with PCI bus.
 - XLR_BIST_BUFFER – write and then read all 512 MB of RAM – checks for bit errors.
 - XLR_BIST_DISK x – x represents the bus number (0-7). This will test all disks present on the specified bus (i.e. master and slave if present).
 - XLR_BIST_ALL – performs complete self-test (PCI, buffer, and all disks present on the system).

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL. Call XLRGetLastError and XLRGetErrorMessage (as demonstrated below) to find which component(s) failed the test.

Diagnostic Error Messages:

Action:

Test of drive that isn't present
 Drive fails self test
 Test of non XF/XF2 StreamStor
 Buffer test failed
 PCI test failed

Error Message:

Invalid command
 Drive missing or failing
 Invalid request for system mode
 Device command failed execution
 Device command failed execution

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrReturnCode;
Char              temp[XLR_ERROR_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRSelfTest( xlrDevice, XLR_BIST_DISK5 );
if( xlrReturnCode != XLR_SUCCESS )
{
    xlrError = XLRGetLastError( );
    XLRGetErrorMessage( temp, xlrError );
    printf( "%s\n", temp );
    exit(1);
}
// Reset the card.
XLRCardReset(1);
```

XLRSetBankMode

Syntax:

```
XLR_RETURN_CODE XLRSetBankMode(SSHANDLE xlrDevice, S_BANKMODE
mode)
```

Description:

XLRSetBankMode sets the banking mode for the StreamStor. By default, the StreamStor device is not in bank mode, i.e., a call to XLROpen will set the bank mode to SS_BANKMODE_DISABLED. (Exceptions to this are the StreamStor PCI-816V100 and PCI-816VXF2 boards, which XLROpen automatically places in bank mode).

The StreamStor remains in the selected mode until a call to XLRSetBankMode is made to change the mode.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *mode* is the constant that defines the banking mode for the StreamStor.
 - SS_BANKMODE_NORMAL – puts the StreamStor into normal bank mode. If BANK_A is ready, it is selected as the current bank. If BANK_A is not ready, then if BANK_B is ready, it is selected as the current bank.
 - SS_BANKMODE_DISABLED – disables bank mode.
 - SS_BANKMODE_AUTO_ON_FULL – automatically switches between banks when one fills up during a recording.
 - SS_BANKMODE_AUTO_ON_SYNC – banks will be automatically switched when one bank nears full (~97%), and then an FPDP SYNC* pulse is received. If no SYNC* pulse is received, banks will NOT be switched.

Autoswitch Notes:

Recording:

When using SS_BANKMODE_AUTO_ON_FULL, StreamStor will switch to the other bank when the current bank becomes full. This transition requires that the bank being switched to is ready, and has not been previously recorded on. For example, if recording begins on Bank A, fills Bank A, and switches to Bank B, StreamStor will not switch back to Bank A unless Bank A has been replaced. If Bank A has been replaced with a new bank, StreamStor will switch back to Bank A when Bank B is full. If Bank A has not been replaced, the recording will end because there is no free space left. Unless the write protect option is set, each call to XLRRecord will prepare each bank present in the system for recording. If the banks have been recorded on before, they will be overwritten. In other words, StreamStor loses its ability to track which banks have been “used” (i.e. written) between calls to XLRRecord. If data written to the bank should not be overwritten, the write protect option should be set on that bank.

Playback:

Auto bank switching is **not** available in playback mode. Any recordings made with auto bank switching will be considered separate recordings for playback. In other words, from a playback perspective (offset and length), each bank begins at an offset of 0. For example, if both banks have been recorded on (such that an autoswitch occurred to Bank B when Bank A filled up), each bank's recording will start at an offset of 0. To start playback at the beginning of Bank A, select Bank A with a call to `XLRSelectBank`, and then begin playback at an offset of 0. To start playback at the beginning of Bank B, select Bank B with a call to `XLRSelectBank`, and then begin playback at an offset of 0.

Note that if you are in bank mode and are using partitions, the bank modes `SS_BANK_AUTO_ON_FULL` and `SS_BANK_MODE_AUTO_ON_SYNC` are not allowed. The only way to begin operations on a different bank is to explicitly select the bank to be used.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

xlrStatus = XLRSetBankMode (xlrDevice, SS_BANKMODE_NORMAL);

//The default bank is Bank A and it is ready, so this call will clear
//write protection on BANK_A.
xlrStatus = XLRclearWriteProtect( xlrDevice );

//Turn bank mode off.
xlrStatus = XLRSetBankMode (xlrDevice, SS_BANKMODE_DISABLED);
```

See Also:

`XLRGetChassisType` and `XLRSelectBank`.

XLRSetDBMode

Syntax:

```
XLR_RETURN_CODE XLRSetDBMode( SSHANDLE xlrDevice, FPDPMODE Mode,
FPDPOP option )
```

Description:

XLRSetDBMode is used to set the operating mode of the external port on the Amazon daughter board (if one exists) or on the FPDP interface for other StreamStor board types. For details on FPDP, please refer to the “External Port” chapter of this manual.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *mode* is a constant that defines the mode of operation.
- *option* is used to modify the operation of the FPDP port.

Please refer to the hardware manual for your StreamStor controller or daughter board for the list of modes and options it supports.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

//
// This example shows how to set various modes and options. Note that
// the manifest constants used differ based on the type of device.
// For example, FPDP/R is SS_FPDPMODE_RECVM for an Amazon daughter
// and is SS_FPDP_RECVMaster for a PCI-816XF2.
//
xlrStatus = XLROpen( 1, &xlrDevice );
...
//
// Select channel 30. Subsequent XLRSetDBMode calls will set
// the options and the modes for the selected channel.
//
xlrStatus = XLRSelectChannel( xlrDevice, 30 );

//
// Example 1: Set the FPDP port mode to FPDP/R and use the default
// options on a PCI-816XF2.
//
xlrStatus = XLRSetDBMode( xlrDevice, SS_FPDP_RECV, 0 );
```

CHAPTER 2 : FUNCTION REFERENCE

```
//  
// Example 2: Enable the data strobe clock and "Not Ready"  
// assert options on a PCI-816XF2 and use FPDP/RM.  
//  
xlrReturnCode = XLRSetDBMode( xlrDevice,  
    SS_FPDP_RECVMaster, SS_OPT_FPDPSTROB|SS_OPT_NRASSERT );  
  
//  
// Example 3: Enable data strobe clock and use FPDP/R on a  
// PCI-816XF2.  
//  
XLRSetDBMode( xlrDevice, SS_FPDP_RECV, SS_OPT_FPDPSTROB );  
  
//  
// Example 4: Enable FPDP/RM mode on a PCI-816XF2, using the  
// default options.  
//  
xlrStatus = XLRSetDBMode( xlrDevice, SS_FPDP_RECVMaster, 0 );  
  
//  
// Example 5: Enable data strobe clock on an Amazon daughter board  
// using FPDP/RM.  
//  
xlrStatus = ( xlrDevice, SS_FPDPMODE_RECVM, SS_DBOPT_FPDPSTROB );  
  
//  
// Example 6: Enable "Not Ready" assert options on an Amazon  
// daughter board and use FPDP/RM.  
//  
xlrReturnCode = XLRSetDBMode( xlrDevice,  
    SS_FPDPMODE_RECVM, SS_DBOPT_FPDPNRASSERT );
```

See Also:

XLRSetMode and XLRSelectChannel.

XLRSetDriveStandbyMode

Syntax:

```
XLR_RETURN_CODE XLRSetDriveStandbyMode( SSHANDLE xlrDevice,
BOOLEAN StandbyEnable)
```

Description:

`XLRSetDriveStandbyMode` is used to put the drives into power standby mode and to take the drives out of power standby mode.

Standby mode is a power management feature that spins-down disk drives. The spindle motor is stopped, and most of the electronics are powered off. Placing drives in standby mode when they are not in use will reduce the power consumption of the drives. This mode also reduces the chance of head-to-disk contact, which greatly decreases the probability of disk damage.

When drives are placed in standby mode, the recovery time when exiting standby mode depends on the disk drive model and other factors.

This command only affects drives that support standby mode, such as 2.5" notebook drives.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to `XLROpen`.
- *StandbyEnable* sets the mode. If *StandbyEnable* is `TRUE`, the drives are put into standby mode. Otherwise, the drives are taken out of standby mode. By default, the drives are not in standby mode.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

xlrStatus = XLROpen( 1, &xlrDevice );

//
// If the enable parameter is TRUE, standby mode will be enabled,
// which means drives should spin down.
//
xlrStatus = XLRSetDriveStandbyMode(xlrDevice, TRUE);

// Do whatever you need to do while the drives are spun down.
. . .
```

CHAPTER 2 : FUNCTION REFERENCE

```
//  
// Now you want to access the drives (for a record or playback,  
// for example). Spin the drives up.  
//  
xlrStatus = XLRSetDriveStandbyMode(xlrDevice, FALSE);  
  
// Sleep 5 seconds, giving the drives time to spin up.  
Sleep(5);  
  
xlrStatus = XLRRecord (xlrDevice, 0, 1);  
    . . .  
  
// Close device before exiting  
XLRClose( xlrDevice );
```

XLRSetLabel

Syntax:

```
XLR_RETURN_CODE XLRSetLabel( SSHANDLE xlrDevice, char *label,  
UINT labelSize )
```

Description:

XLRSetLabel sets the label on the StreamStor recorder. The drives must be idle (i.e., no recording or playback in progress) to set a label.

Note that if you call XLRERase to erase a recorder, whether or not the label is erased depends on the erase option you specify. Also, note that the length returned by XLRGetLength and by XLRGetDirectory does not include the length of the label.

If the StreamStor is in bank mode, this command will set the label for the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *label* is a pointer to a null terminated string no more than XLR_LABEL_LENGTH in size (including the NULL).
- *labelSize* is the length of label, not including the NULL terminator. If *labelSize* is 0 (zero), the label on the device will be null'ed out.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;
char              label[XLR_LABEL_LENGTH];

xlrStatus = XLROpen( 1, &xlrDevice );

strcpy (label, "Volume 1, 19-April-2004");
xlrStatus = XLRSetLabel( xlrDevice, "Volume 1, label, strlen(label));
...
xlrStatus = XLRGetLabel( xlrDevice, label );
printf ( "This disk set is labeled %s\n", label );
...
// Null out the label.
xlrStatus = XLRSetLabel( xlrDevice, "", 0 );
...
// Close device before exiting
XLRclose( xlrDevice );
```

See Also:

XLRGetLabel, XLRerase, XLRSetBankMode and XLRselectBank.

XLRSetMode

Syntax:

```
XLR_RETURN_CODE XLRSetMode( SSHANDLE xlrDevice, SSMODE Mode )
```

Description:

XLRSetMode is used to set the input/output path and functionality of StreamStor.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *Mode* is a constant that defines the mode of StreamStor operation.
- Possible mode values are:
 - SS_MODE_SINGLE_CHANNEL - This is the default mode that receives and sends data over one channel – i.e. the PCI bus, or one of the external ports.
 - SS_MODE_FORK - This mode allows data to be recorded and simultaneously output. For example, data can be coming in over one of the external ports, recorded, and sent out the other external port.
 - SS_MODE_PASSTHRU - This mode is identical to SS_MODE_FORK except that the data is not recorded; data merely passes in one port and out the other.
 - SS_MODE_MULTI_CHANNEL - This mode allows StreamStor to record data from multiple input channels simultaneously. For example, data can be coming in from the external port and the PCI bus at the same time.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Note: **CHANGING MODES CLEARS ALL INPUT AND OUTPUT CHANNELS. CHANNELS MUST BE BOUND AFTER THE MODE IS SELECTED.**

Usage:

```
SSHANDLE xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...
// Set StreamStor to use the external port
xlrReturnCode = XLRSetMode( xlrDevice, SS_MODE_SINGLE_CHANNEL );
```

See Also:

XLRSetDBMode, XLRBindInputChannel and XLRBindOutputChannel.

XLRSetPlaybackLength

Syntax:

```
XLR_RETURN_CODE XLRSetPlaybackLength( SSHANDLE xlrDevice, ULONG  
lenHigh, ULONG lenLow )
```

Description:

XLRSetPlaybackLength is used to stop playback after a specified number of bytes have been played. When a playback length is set, playback continues until the number of specified bytes has been played, XLRStop is called or all data has been played. The playback length remains in effect until the next XLROpen or until XLRSetPlaybackLength is called again.

The playback length is used by the XLRPlayback, XLRRead and XLRReadToPhy commands. Playback length is initially set to zero by XLROpen. A playback length of zero causes playback or reading to continue until all data is played or read. Note that each time you call XLRPlayback, XLRRead or XLRReadToPhy, the count of the number of bytes that have already played returns to zero.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *lenHigh* is the upper 32 bits of the 64 bit value that identifies the playback length.
- *lenLow* is the lower 32 bits of the 64 bit value that identifies the playback length.

The playback length must be an eight byte-aligned value.

Return Value:

On success, this function returns XLR_SUCCESS.
On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;
DWORDLONG   bytesToPlay;
ULONG       lenHigh;
ULONG       lenLow;
S_DEVSTATUS devStatus;

bytesToPlay = 1048576;

xlrStatus = XLROpen( 1, &xlrDevice );
    ...

//lenHigh and lenLow must represent an 8 byte aligned address.
lenHigh = bytesToPlay >> 32;
lenLow = bytesToPlay & 0xFFFFFFFF;
xlrReturnCode = XLRSetPlaybackLength( xlrDevice, lenHigh, lenLow );

// Start playback (at the beginning of the recording in this example).
// Poll every 10 seconds to see if playback has stopped.
// Note: if you use polling to check status, the more often you poll,
// the greater the impact on performance.

XlrReturnCode = XLRPlayback( xlrDevice, 0,0 );

do {
    ... sleep for 10 seconds, then poll device status ...
    XlrReturnCode = XLRGetDeviceStatus ( xlrDevice, &devStatus );
} while (devStatus.Playing == TRUE);
```

See Also:

XLRPlayback, XLRGetPlayLength, XLRSetMode, XLRSetDBMode,
XLRSetBankMode and XLRSelectBank.

XLRSetPortClock

Syntax:

```
XLR_RETURN_CODE XLRSetPortClock( SSHANDLE xlrDevice, UINT clock )
```

Description:

XLRSetPortClock is used to set the operating frequency of the external port if applicable.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *clock* is a constant that defines the desired clock frequency. Possible values are defined in the header file `xlrdbcommon.h` as `SS_PORTCLOCK_xMHz` values. The FPDP clock is programmable from 6 MHz up to 50 MHz.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
// Set the external clock frequency
SSHANDLE xlrDevice;

xlrStatus = XLROpen( 1, &xlrDevice );
...

xlrReturnCode = XLRSetPortClock( xlrDevice, SS_PORTCLOCK_40MHZ );
```

XLRSetReadLimit

Syntax:

```
XLR_RETURN_CODE XLRSetReadLimit( SSHANDLE xlrDevice, ULONG Limit
 )
```

Description:

`XLRSetReadLimit` sets the size of the address range an outside device will be using when reading data from `StreamStor` during playback (`XLRPlayback`). This is required to prevent `StreamStor` hardware from discarding cached read data when an external DMA engine recycles to a new starting read address on the PCI bus.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to `XLROpen`.
- *Limit* is the address range size that the outside device will use when reading from `StreamStor` during playback operations.

Return Value:

On success, this function returns `XLR_SUCCESS`.

On failure, this function returns `XLR_FAIL`.

Usage:

```
SSHANDLE xlrDevice;
ULONG DMA_size = 0x2000;
PULONG pBuffer;
PULONG pSSAddr;

xlrStatus = XLROpen( 1, &xlrDevice );
...
// Put StreamStor into Playback mode at beginning of recording
xlrReturnCode = XLRSetReadLimit( xlrDevice, DMA_size );
xlrReturnCode = XLRPlayback( xlrDevice, 0, 0 );

// Outside device can now DMA data from StreamStor within an
// address range size defined by DMA_size.
// The following simulates this by reading from StreamStor to memory.
pBuffer = (PULONG)malloc(DMA_size);
pSSAddr = XLRGetWindowAddr( xlrDevice );

for( j = 0; j < loops; j++ )
{
    for( i = 0; i < DMA_size; i += 4 )
    {
        *pBuffer++ = *pSSAddr++;
    }
}
```

XLRSetUserDir

Syntax:

```
XLR_RETURN_CODE XLRSetUserDir( SSHANDLE xlrDevice, PVOID udirPtr,
    UINT udirSize )
```

Description:

XLRSetUserDir sets the user directory on the StreamStor recorder. The drives must be idle (i.e., no recording or playback in progress) to set the user directory.

If the StreamStor is in bank mode, this command will set the user directory only on the selected bank. If the StreamStor is partitioned, this command will create a user directory on the selected partition.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *udirPtr* is a pointer to the buffer containing the user directory. The buffer can contain any type of data (string, binary, etc.). The maximum size of the user directory is XLR_MAX_UDIR_LENGTH.
- *udirSize* is the size (in bytes) of the buffer pointed to by *udirPtr*. If *udirSize* is zero, then *udirPtr* is ignored and any existing user directory will have its length set to zero. The user directory must be 8 byte aligned (i.e., its *udirSize* must be a multiple of 8).

Note: This command can be very slow over the remote interface.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE  xlrStatus;
char              userDirBuff[4800];
UINT              dirLength;

// Open the device
xlrStatus = XLROpen(1, &xlrDevice);
strcpy (userDirBuff, "1234567");
//Add 1 to length for the NULL terminating character.
dirLength = strlen(userDirBuff) + 1;
xlrStatus = XLRSetUserDir(xlrDevice, userDirBuff, dirLength);
```

See Also:

XLRGetUserDir, XLRGetUserDirLength, XLRSetBankMode and XLRSelectBank.

XLRSetWriteProtect

Syntax:

```
XLR_RETURN_CODE XLRSetWriteProtect( SSHANDLE xlrDevice )
```

Description:

XLRSetWriteProtect marks a StreamStor recorder as write protected. After write protection is set, subsequent attempts to alter the recorded data (i.e., calls to XLRRecord, XLRAppend or XLRERase) will return an error. The drives must be idle (i.e., no recording or playback in progress) to set the write protection.

Physical removal and reinsertion of the drives will not change the write protection. The only way to remove the write protection is to call XLRClearWriteProtect.

By default, drives are not write protected. The drives must be idle (i.e., no recording or playback in progress) to set the write protection.

If the StreamStor is in bank mode, this command will set write protection only on the selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

//
//We know we want to reuse these disks and that they were previously
//write protected. Clear the protection so we can erase the drives
//and start a fresh recording.
xlrStatus = XLRClearWriteProtect( xlrDevice );
xlrStatus = XLERase( xlrDevice, SS_OVERWRITE_NONE );

//Start recording.
xlrStatus = XLRRecord ( xlrDevice, 0,1 );
...
xlrStatus = XLRStop( xlrDevice );

//Write protect this recording.
xlrStatus = XLRSetWriteProtect( xlrDevice );
...
// Close device before exiting
XLRClose( xlrDevice );
```

See Also:

XLRClearWriteProtect, XLRGetBankStatus, XLRSetBankMode and
XLRSelectBank.

XLRStop

Syntax:

```
XLR_RETURN_CODE XLRStop( SSHANDLE xlrDevice )
```

Description:

XLRStop will halt a recording operation and make sure all data is flushed to disk. This function should always be used to end a recording.

XLRStop can also be used to halt a playback initiated by XLRPlayback.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE xlrDevice;  
  
xlrStatus = XLROpen( 1, &xlrDevice );  
...  
xlrReturnCode = XLRStop( xlrDevice );
```

See Also:

XLRRecord, XLRAppend and XLRPlayback.

XLRTtruncate

Syntax:

```
XLR_RETURN_CODE XLRTtruncate( SSHANDLE xlrDevice, ULONG AddrHigh,
ULONG AddrLow )
```

Description:

XLRTtruncate will truncate an existing recording at the address provided. The address must fall within the bounds of the currently recorded data set.

The truncation address must be an eight byte-aligned value.

If the StreamStor is in bank mode, this command will truncate data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *AddrHigh* is the upper 32 bits of the 64-bit truncation address.
- *AddrLow* is the lower 32 bits of the 64-bit truncation address.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE          xlrDevice;
XLR_RETURN_CODE   xlrStatus;
ULONG             AddrHi;
ULONG             AddrLo;

// Open the device
xlrStatus = XLROpen( 1, &xlrDevice );

// Append data
xlrStatus = XLRAppend( xlrDevice );
.
.
.
// Stop recording
XLRStop( xlrDevice );

//AddrHi and AddrLo must represent an appropriately aligned address.
AddrHi = 0;
AddrLo = 0xFE120000;

// Truncate the recording.
xlrStatus = XLRTtruncate( xlrDevice, AddrHi, AddrLo );
```

CHAPTER 2 : FUNCTION REFERENCE

```
// Close device before exiting  
XLRClose( xlrDevice );
```

See Also:

XLRDeleteAppend, XLRSetBankMode and XLRSelectBank.

XLRWrite

Syntax:

```
XLR_RETURN_CODE XLRWrite( SSHANDLE xlrDevice, PS_READDESC
pWriteDesc)
```

Description:

XLRWrite writes data from a user memory buffer to StreamStor. StreamStor must be in record mode (XLRRecord or XLRAppend) before calling this function.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *pWriteDesc* is a pointer to an S_READDESC structure that holds the length and buffer address of the write data. Note that the AddrHigh and AddrLow parameters are ignored.

If the StreamStor is in bank mode, this command will write data to the currently selected bank.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE      xlrDevice;
S_READDESC    writeDesc;
ULONG         myBuffer[40000];

writeDesc.XferLength = sizeof( myBuffer );
writeDesc.BufferAddr = myBuffer;

// Open StreamStor.
if( XLROpen( &xlrDevice, 1 ) != XLR_SUCCESS )
    return(1);

//Put StreamStor into record mode.
if( XLRRecord( xlrDevice, 0, 1 ) != XLR_SUCCESS )
    return(1);

/* Fill the memory here . . . */

// Write the buffer to StreamStor.
if( XLRWrite( xlrDevice, &writeDesc ) != XLR_SUCCESS )
    return(1);
```

See Also:

XLRRecord, XLRAppend, XLRWriteData, XLRSetMode, XLRSetBankMode and XLRSelectBank.

XLRWriteData

Syntax:

```
XLR_RETURN_CODE XLRWriteData( SSHANDLE xlrDevice, PVOID BufAddr,
ULONG TransferSize )
```

Description:

XLRWriteData is identical to XLRWrite except that the parameters are not passed in a structure.

If the StreamStor is in bank mode, this command will write data from the currently selected bank.

Parameters:

- *xlrDevice* is the device handle returned from a previous call to XLROpen.
- *BufAddr* is a pointer to the buffer to be written to StreamStor.
- *TransferSize* is the number of bytes to write.

Return Value:

On success, this function returns XLR_SUCCESS.

On failure, this function returns XLR_FAIL.

Usage:

```
SSHANDLE    xlrDevice;
ULONG       myBuffer[40000];

xlrStatus = XLROpen( 1, &xlrDevice );
...
xlrReturnCode = XLRWriteData( xlrDevice, myBuffer, sizeof(myBuffer) );
```

See Also:

XLRRecord, XLRAppend, XLRWrite, XLRSetMode, XLRSetBankMode and XLRSelectBank.

Structure S_BANKSTATUS

```
typedef struct _BANKSTATUS
{
    char            Label[XLR_LABEL_LENGTH];
    DWORDLONG      Length;
    UINT           State;
    UINT           Selected;
    UINT           PowerRequested;
    UINT           PowerEnabled;
    UINT           MediaStatus;
    UINT           WriteProtected;
    UINT           ErrorCode;
    UINT           ErrorData;
    UINT           TotalCapacity;
} S_BANKSTATUS, *PS_BANKSTATUS;
```

Purpose

This structure is used by the `XLRGetBankStatus` function to return data about the StreamStor bank status of the specified bank.

Members

- *Label* - String holding the bank label.
- *Length* - Length of the bank's recording (in bytes).
- *State* - A bank can be in any of 3 states: `STATE_READY`, `STATE_NOT_READY`, and `STATE_TRANSITION`. If the state is `STATE_READY`, the bank is ready for use. Otherwise, it is not ready, or it is transitioning to or from a ready or not ready state.
- *Selected* - If `TRUE`, the specified bank is the currently selected bank.
- *PowerRequested* - If `TRUE`, a power up request has been received for the bank. Otherwise, a request has not been received.
- *PowerEnabled* - If `TRUE`, the bank has power. Otherwise, it does not.
- *MediaStatus* - There are four possible values:
 - `MEDIASTATUS_EMPTY` - indicates that the bank has no data recorded on it.
 - `MEDIASTATUS_NOT_EMPTY` - indicates that the bank has some data recorded on it but it is not full.
 - `MEDIASTATUS_FULL` - indicates that the bank is full.
 - `MEDIASTATUS_FAULTED` - indicates that there is data on the bank, but for some reason the directory structure is corrupted. The bank must be erased before it can be used.
- *WriteProtected* - If `TRUE`, the bank is write protected. Otherwise, the bank is not write protected.

CHAPTER 2 : FUNCTION REFERENCE

- *ErrorCode* – If 0 (zero), an error has not been detected on the bank. Otherwise, it is set to the error code.
- *ErrorData* – If *ErrorCode* is non-zero, *ErrorData* holds any additional data about the error.
- *TotalCapacity* – The bank's capacity in system pages.

Structure S_DBINFO

```
typedef struct _DBINFO
{
    UINT SerialNum;
    char PCBVersion[XLR_VERSION_LENGTH];
    char PCBType[XLR_MAX_NAME];
    char PCBSubType[XLR_MAX_NAME];
    char FPGAConfig[XLR_MAX_NAME];
    char FPGAConfigVersion[XLR_VERSION_LENGTH];
    UINT NumChannels;
    UINT Param[8];
} S_DBINFO, *PS_DBINFO;
```

Purpose

This structure is used by the XLRGetDBInfo function to return data about the daughter board.

Members

- *SerialNum* – the daughter board serial number.
- *PCBVersion* – the daughter board version.
- *PCBType* – the daughter board type.
- *PCBSubType* – the daughter board subtype.
- *FPGAConfig* – the function type of the code loaded in the FPGA on the daughter board.
- *FPGAConfigVersion* – the version of the code loaded in the FPGA on the daughter board.
- *NumChannels* – the number of channels on the daughter board.
- *Param* - Reserved for future use.

Structure S_DEVINFO

```
typedef struct _DEVINFO
{
    char        BoardType[XLR_MAX_NAME];
    UINT        SerialNum;
    UINT        NumDrives;
    UINT        NumBuses;
    UINT        TotalCapacity;
    UINT        MaxBandwidth;
    UINT        PciBus;
    UINT        PciSlot;
    UINT        NumExtPorts;
}S_DEVINFO, *PS_DEVINFO;
```

Purpose

This structure is used by the XLRGetDeviceInfo function to return data about the StreamStor system configuration.

Members

- *BoardType* - the board type (model name).
- *SerialNum* - the serial number of the StreamStor board.
- *NumDrives* - the number of drives currently connected and configured on the StreamStor controller.
- *NumBuses* – the number of ATA buses in use.
- *TotalCapacity* - the total recording capacity of the StreamStor system in system pages (a page is 4096 bytes typically on Intel based Windows systems).
- *MaxBandwidth* – Reserved.
- *PciBus* - the PCI bus number to which the StreamStor is connected.
- *PciSlot* – the PCI slot number to which the StreamStor is connected.
- *NumExtPorts* – the number of external ports.

Structure S_DEVSTATUS

```
typedef struct _DEVSTATUS
{
    BOOLEAN SystemReady;
    BOOLEAN BootmonReady;
    BOOLEAN Recording;
    BOOLEAN Playing;
    BOOLEAN Reserved1;
    BOOLEAN Reserved2;
    BOOLEAN Reserved3;
    BOOLEAN Reserved4;
    BOOLEAN RecordActive[XLR_MAX_VRS];
    BOOLEAN ReadActive[XLR_MAX_VRS];
    BOOLEAN FifoActive;
    BOOLEAN DriveFail;
    UINT    DriveFailNumber;
    BOOLEAN SysError;
    UINT    SysErrorCode;
    BOOLEAN Booting;
    BOOLEAN FifoFull;
    BOOLEAN Overflow[XLR_MAX_VRS];
}S_DEVSTATUS, *PS_DEVSTATUS;
```

Purpose

This structure holds various system status flags as returned by the XLRGetDeviceStatus function.

Note: The array index value is always 0 for RecordActive, ReadActive, VRActive, and Overflow

Members

- *SystemReady* – System ready flag, indicates the system firmware and hardware have been initialized successfully.
- *BootmonReady* – Power on boot flag, indicates that the system boot succeeded and the system is ready for initialization (XLROpen).
- *Recording* – Indicates that the system is currently in a record mode.
- *Playing* – Indicates that the system is currently in a playback mode.
- *Reserved1, Reserved2, Reserved3 and Reserved4* – not used.
- *RecordActive* – If not in bank mode, element 0 indicates that the system is currently recording. If in bank mode, element 0 indicates that BANK A is currently recording and element 1 indicates that BANK B is currently recording.
- *ReadActive* – If not in bank mode, element 0 indicates that the system is currently reading. If in bank mode, element 0 indicates that BANK A is currently reading and element 1 indicates that BANK B is currently reading.

CHAPTER 2 : FUNCTION REFERENCE

- *FifoActive* – Indicates that the system is currently in FIFO mode.
- *DriveFail* – Indicates that a drive has failed.
- *DriveFailNumber* – Indicates the drive that has failed. Valid when *DriveFail* is TRUE.
- *SysError* – Indicates that system initialization failed.
- *SysErrorCode* – Holds initialization error code if *SysError* is TRUE.
- *Booting* – For Conduant internal use only.
- *FifoFull* – Indicates the system is at capacity while in FIFO mode.
- *Overflow* – Indicates the disk drives reached capacity during a record operation. When in mode *SS_MODE_FORK* or *SS_MODE_PASSTHRU* (see *XLRSetMode*), *Overflow* gets set when the external port data has overflowed the available FIFO space.

Structure S_DIR

```
typedef struct _DIR
{
    DWORDLONG    Length;
    DWORDLONG    AppendLength;
    BOOLEAN      Full;
    BOOLEAN      WriteProtected;
}S_DIR, *PS_DIR;
```

Purpose

This structure holds the directory information for the current recording. The structure is filled with a call to `XLRGetDirectory`. Use `XLRGetLengthPages` for environments that can't support 64 bit integers (`DWORDLONG`).

Members

- *Length* – The length of the current recording in bytes. Note that this parameter is a 64 bit number.
- *AppendLength* – The length of the last set of data recorded using `XLRAppend`. Note that this parameter is a 64-bit number.
- *Full* – This flag will be `TRUE` (non-zero) when the system has been filled to capacity.
- *WriteProtected* – If not in bank mode, this flag will be `TRUE` (non-zero) if the system is write protected. If the system is in bank mode, this flag will be `TRUE` if the currently selected bank is write protected.

Structure S_DRIVEINFO

```
typedef struct _DRIVEINFO
{
    char    Model[XLR_MAX_DRIVENAME];
    char    Serial[XLR_MAX_DRIVESERIAL];
    char    Revision[XLR_MAX_DRIVEREV];
    UINT    Capacity;
    BOOLEAN SMARTCapable;
    BOOLEAN SMARTState;
}S_DRIVEINFO, *PS_DRIVEINFO;
```

Purpose

This structure holds information about a disk drive installed in the system. The structure is filled with a call to `XLRGetDriveInfo`.

Members

- *Model* – Model name as reported by the disk drive identify command.
- *Serial* – Drive serial number as reported by the disk drive identify command.
- *Revision* – Drive revision level as reported by the disk drive identify command.
- *Capacity* – Drive capacity as reported by identify command. Value is number of 512 byte sectors.
- *SMARTCapable* – Indicates whether the drive has “SMART” capabilities. SMART is Self-Monitoring Analysis and Reporting Technology. You can query drives with this technology and determine if they are faulty. If *SMARTCapable* is TRUE, the drive has this feature. Otherwise, the drive does not have this feature.
- *SMARTState* - On drives that are *SMARTCapable*, this structure member is used to indicate the drive’s state. If *SMARTState* is TRUE, the drive is good. Otherwise, the drive is faulty. The value of this structure member is only valid if *SMARTCapable* is TRUE.

Structure S_PARTITIONINFO

```
typedef struct _PARTITIONINFO{
    BOOLEAN Partitioned;
    UINT    NumPartitions;
    UINT    SpaceAllocated;
    UINT    SpaceAvailable;
    UINT    SelectedPartition;
    UINT    PartitionCapacity;
}S_PARTITIONINFO, *PS_PARTITIONINFO;
```

Purpose

This structure is used to return information on both the selected partition and remaining space.

Members

- *Partitioned* – Indicates whether StreamStor is currently partitioned or not.
- *NumPartitions* – The number of partitions currently on StreamStor.
- *SpaceAllocated* – The number of pages currently allocated in partitions (all partitions not just the currently selected partition).
- *SpaceAvailable* – The number of pages of unpartitioned space available.
- *SelectedPartition* – Currently selected partition.
- *PartitionCapacity* – Size of the selected partition in pages.

Structure S_READDESC

```
typedef struct _READDESC{
    PULONG   BufferAddr;
    ULONG    AddrHi;
    ULONG    AddrLo;
    ULONG    XferLength;
}S_READDESC, *PS_READDESC;
```

Purpose

This structure is used to define the parameters for a read from or a write to the StreamStor. (See, for example, XLRRead and XLRWrite).

Members

- *BufferAddr* – Address of buffer to hold data read from StreamStor. Must be at least *XferLength* bytes.
- *AddrHi* – High word (32 bit) of starting byte address.
- *AddrLo* – Low word (32 bit) of starting byte address.
- *XferLength* – Number of bytes to transfer from StreamStor.

Structure S_XLRSWREV

```
typedef struct _XLRSWREV
{
    char    ApiVersion[XLR_VERSION_LENGTH];
    char    ApiDateCode[XLR_DATECODE_LENGTH];
    char    FirmwareVersion[XLR_VERSION_LENGTH];
    char    FirmDateCode[XLR_DATECODE_LENGTH];
    char    MonitorVersion[XLR_VERSION_LENGTH];
    char    XbarVersion[XLR_VERSION_LENGTH];
    char    AtaVersion[XLR_VERSION_LENGTH];
    char    UAtaVersion[XLR_VERSION_LENGTH];
    char    DriverVersion[XLR_VERSION_LENGTH];
}S_XLRSWREV, *PS_XLRSWREV;
```

Purpose

This structure is used by `XLRGetVersion` to return software/hardware version strings.

Members

- *ApiVersion* – Version of the StreamStor API library.
- *ApiDateCode* – Build date of the StreamStor API library.
- *FirmwareVersion* – StreamStor firmware version.
- *FirmDateCode* – Build date of the firmware.
- *MonitorVersion* – Boot monitor firmware version.
- *XbarVersion* – Controller logic version.
- *AtaVersion* – ATA controller version.
- *UAtaVersion* – Ultra ATA controller version.
- *DriverVersion* – Driver version.

Chapter 3

PCI Integration

PCI Integration

To allow maximum bandwidth for recording digital data over the PCI bus, StreamStor is designed for direct card-to-card data transfers. Since many data acquisition cards already perform DMA operations directly to system memory, the StreamStor controller uses this capability for the direct transfer of data. The software development kit provides the necessary control functions for integration of StreamStor into user applications.

Initialization and Setup

Initialization requires a call to the `XLROpen` function. This function will lock the device for exclusive access and initialize the recording system. The initialization routine includes locating the StreamStor controller on the PCI bus, downloading software and initializing required data structures, etc.

PCI Bus Interfacing

Although the PCI bus itself has been designed for card-to-card transactions, most operating systems have no provisions for this functionality. In addition, most operating systems do not have provisions for real-time event management, which is required when recording data at high bandwidths. For these reasons, there may be a requirement to modify existing device drivers for the PCI card that is to send data to the StreamStor system.

The StreamStor controller requests a memory mapped window during computer booting providing a memory space for writing data to be recorded. The default size of this window is 8MB although you should use the `XLRGetBaseRange` to verify this in your application. The StreamStor SDK provides two functions that return the physical and logical addresses of this window.

The address returned by `XLRGetBaseAddr` is the physical address that is assigned to the StreamStor data window during the boot process. The StreamStor PCI interface chip will respond to any memory writes on the PCI bus in this address range. Note, however, that the StreamStor system does not utilize the address to determine where to store the data. Any data writes are recorded to disk in the order they are received. This physical address can be used directly for programming DMA hardware on the PCI data source device. Various techniques can be used for programming the DMA hardware but generally you will need to set up a DMA block transfer that continuously recycles back to the original starting address. If the DMA hardware supports chaining (scatter/gather) then a looping transfer can be set up. Consult the documentation for your PCI data acquisition card for more information.

⚠ CAUTION: *The physical address returned by `XLRGetBaseAddr` cannot be used in place of a buffer memory address. Use `XLRGetWindowAddr` instead.*

The address returned by `XLRGetWindowAddr` is a logical address created by the operating system to “map” the physical address space of the StreamStor controller into the application memory space. This address can sometimes be used with software provided by PCI card vendors in place of the address of a memory buffer. Check with Conduant about your specific environment for more details. In addition, “writing” to this address space from an application is an effective method to save application specific directory or indexing information about the recording. It is the responsibility of the user application to manage this type of data.

Multi-Card Operation

Multiple StreamStor cards can be used in a single system either on the same bus or on “bridged” PCI buses. If multiple StreamStor cards are installed into the same bus there will be contention for ownership of the bus during data transfers and the effective bandwidth will be reduced. If multiple StreamStor cards are installed on opposite sides of a PCI-PCI bridge than there is no loss in bandwidth as long as the data capture card is co-located on the same bus as the StreamStor card it is streaming data to.

Software applications gain exclusive access to a StreamStor card after calling the `XLROpen` function. Until the application exits or calls `XLRClose`, no other application may connect to that StreamStor card. A single application can connect to and control multiple StreamStor cards but must manage the unique handles returned from multiple calls to the `XLROpen` function. The index number passed into `XLROpen` determines which card is to be controlled by the handle returned. If multiple applications (or multiple instances of the same application) are used to control StreamStor cards, they must each connect to a unique StreamStor card. The `XLRDeviceFind` function returns the number of StreamStor devices found in the system. The index number cannot be larger than this number. In most cases, the higher value index indicates a card that is on a bus or slot further from the main bus. The PCI bus number and slot number are available from the `XLRGetDeviceInfo` command. The command can be used to identify the appropriate card in a multi-card system.

Chapter 4

Operation

Operation

The operation of StreamStor for recording data is very similar to the familiar interface of a tape recorder. The `XLRRecord` function puts the recorder into record mode and the `XLRStop` function ends the recording. Data reading is more like a traditional computer storage device since the data can be retrieved randomly. The StreamStor recorder also has a special “wrap” mode to allow continuous recording past the capacity limits of the disks by overwriting the oldest data.

Data Recording

After getting the base address of the data window using `XLRGetBaseAddr`, it is used to setup the DMA hardware on the data acquisition card for direct slave writing to the StreamStor controller. Because the capacity available on StreamStor is much larger than the 32 bit PCI address scheme (4 GB) will allow, the system is designed to ignore PCI addressing and assume any data written within the PCI address range is data to be recorded sequentially. The actual size of the data window can be found with a call to `XLRGetBaseRange` (default: 8MB). The PCI data source card is required to maintain a destination address within this range. This can easily be accomplished with DMA chaining or other techniques. For example, the data acquisition card can be programmed to start at the base address, write 64kB, then start over again at the base address for the next 64kB, etc.

Recording Data

To start a recording the application must call the `XLRRecord` function. Once `XLR_SUCCESS` status has been returned from this function, StreamStor will record all data written to its data address range. This function should be called BEFORE starting the flow of data to prevent overflow on the data source device. The user application can periodically sample the device status using `XLRGetDeviceStatus` to check for errors that occurred during recording. Note that this function call generates PCI traffic and can impact data transfer bandwidth if used excessively.

Many data acquisition cards have operating modes that allow the capture of a specific number of data points. Unfortunately, the software does not usually allow specifying a number larger than a 32-bit integer (4,294,967,295). For this reason it may be necessary to use the data acquisition card in a “pre-trigger” mode where data is captured continuously until the trigger and then a specified number of data points are captured after the trigger. The data acquisition card will then continuously cycle through its “memory buffer” until receiving the trigger. StreamStor will continuously record all of the data, however, up to its full capacity. To use the recorder in this fashion, you should enable the “Wrap” feature in the `XLRRecord` function so that StreamStor will overwrite the oldest data if the disk system is full.

In order to capture the maximum amount of data without overwriting old data the StreamStor system is designed to “exit” record mode when the disk subsystem is filled to capacity (unless “Wrap” has been set). The user application can poll the device status using `XLRGetDeviceStatus` watching for `Recording` to go `FALSE`. A normal `XLRStop` command should then be used to end record mode. Note that the StreamStor controller is designed to accept data on the PCI bus even after the disk subsystem is full to prevent system errors and allow you to shut down the data source after completely filling the available disk space.

Data Wrap

In some recording applications, it is desirable to continue recording past the capacity of the recording system by overwriting the oldest recorded data. This is sometimes called “pretrigger” or “circular” recording. The StreamStor system supports this recording mode by setting the “Wrap” bit in the `XLRRecord` command. The recorder will continue to record after the disk capacity is exhausted by overwriting the oldest data on the disks. Once the recording is finally stopped, the `XLRGetLength` command can be used to determine how much data has been recorded. If your data is blocked in anything other than 4 byte blocks, you will need to index back from the end of the data to find an aligned start point of your data. Contact technical support for more information on using this feature.

Ending the Recording

If storage wrapping mode has not been enabled, StreamStor will continue to record data until all recording space has been exhausted or the `XLRStop` function has been called. If the `XLRStop` function is not used, any data written to the StreamStor data range after space is exhausted will be lost.

If data wrapping has been enabled, StreamStor will continue to record data indefinitely until the `XLRStop` function is called. When free storage space has been exhausted, the system will begin to overwrite the oldest data so that the newest data is kept.

☞ **NOTE:** *A data acquisition system can stop recording by simply ceasing any writes to the StreamStor data address range. The `XLRStop` function should still be used to flush all data to the disk drives and to prepare for reading of the data.*

Data Read

Because operating systems cannot handle the massive file sizes resulting from a long recording, the SDK provides a read function for retrieving data from the recorder. The user application must supply a memory buffer sufficient to hold the data requested. Note that the StreamStor system will have optimum read performance when reading is performed sequentially from the device.

Read Setup

The StreamStor device must be previously opened with `XLROpen` before reading data or performing other operations.

If the recording was done with wrapping enabled (old data may be overwritten), use the `XLRGetLength` command to get an accurate count of the bytes recorded. This number can then be used for indexing into the data.

Read Positioning

A structure is used to set the read pointer with a byte-offset count. A high and low value is used to overcome the 32 bit limitations of some programming environments.

Reading Data

An `XLRRead` command is used to request a data transfer from StreamStor to system memory.

Chapter 5

External Port

External Port

Some models of StreamStor include additional connectors and electronics to provide an alternate method of transferring data into and out of StreamStor. These additional paths offer several advantages, including:

- freedom from interaction with other devices on an arbitrated bus such as PCI;
- the reduction or elimination of bus FIFOs that may otherwise be required to interface with an arbitrated bus;
- full isolation of data path from operating system and computer hardware facilitates predictable and repeatable behavior;
- better or additional control over timing and other parameters;
- higher bus utilization efficiency due to non-arbitrated nature;
- access to interface signals without risk of crashing host computer;
- higher data rates than the most common PCI buses support; and
- the potential for dual-port operation (simultaneous transfers on both PCI bus and external ports) while recording or playing back.

FPDP

Overview

The FPDP (Front Panel Data Port) external port feature is included on a variety of StreamStor controllers. The hardware manual for your StreamStor controller or daughter board will indicate if FPDP is supported on it and will provide any other model-specific details.

FPDP is a 32-bit synchronous data bus that allows data to be transferred at high speeds between devices. Simple and low-cost in its implementation, FPDP supports the necessary flow controls to manage transfers between devices of different speeds. The sustained speed on the StreamStor interface varies, depending on the StreamStor controller model.

In reading the following sections on using this feature, it is important to be familiar with the American National Standard for Front Panel Data Port Specifications (ANSI/VITA 17-1998). This manual is intended to clarify StreamStor's operation as it relates to the standard, not to educate one on the standard itself. For additional information about the standard, other FPDP products and manufacturers, and other technical details regarding FPDP, please visit www.fdp.com.

The StreamStor FPDP interface is designed to meet and exceed the basic capabilities of FPDP as defined in the FPDP ANSI standard. The following sections describe:

- any optional FPDP features StreamStor has implemented;
- any features that StreamStor has implemented as a superset to the standard;
- any known deviations from the ANSI standard;
- any clarifications that might otherwise be left open to interpretation; and
- the API functions necessary to configure an external port.

Interface Electronics

Interface electronics and termination values on StreamStor are those recommended by the ANSI standard, though some signals and terminations can be electronically connected or isolated with crossbar switching devices in order to support electronic reconfiguration.

Data Formats

The FPDP is a multi-drop bus intended to carry either framed or unframed data. StreamStor currently supports only the unframed data mode. The SYNC* (Sync Pulse) signal is driven to an inactive state while StreamStor is a data transmitter on the FPDP bus.

Contact Conduant for more information on using framed data.

PIO Signals

PIO signals are programmable lines for I/O for user-defined functions. These are ancillary signals and are not required for the FPDP function. StreamStor currently does not drive or act on received PIO signals. Contact Conduant for more information on using PIO signals.

Interface Functions

To ready StreamStor to transfer data using FPDP, the API routine `XLRBindxxxChannel` must be called. The FPDP port's channel number will depend on the board type. (For details on channel numbers, see the `XLRSelectChannel` function in the Function Reference section of this manual.) The bind function is called as follows (`xxx` stands for "Input" or "Output" depending on intended usage):

```
XLRBindxxxChannel ( device, 0 );
```

After StreamStor is in external port mode, an API call to `XLRSetDBMode` is used to configure the port. This command allows you to set the mode to one of:

- FPDP Transmit Master (FPDP/TM)
- FPDP Transmit (FPDP/T, StreamStor unique)
- FPDP Receive (FPDP/R)
- FPDP Receive Master (FPDP/RM).
- FPDP Receive Master Clock Master (FPDP/RMCM, StreamStor unique)

In FPDP/T mode, StreamStor drives the FPDP DATA, DVALID* (Data Valid), DIR* (direction), and SYNC* (Sync Pulse) signals but uses the FPDP clock that is driven to the FPDP bus by some other source. In this mode,

StreamStor does not provide any termination for signals other than DATA¹. To use this mode properly, StreamStor should NOT be positioned at either end of the FPDP bus. Note also that the maximum useable frequency in this mode will decay more rapidly as the cumulative distance from the clock source to the data source to the data destination increases.

In FPDP/RMCM mode, StreamStor acts as a Receive Master, excepting that StreamStor also drives the FPDP clock signals on the FPDP bus. In addition, StreamStor terminates the clock signals (PSTROBE, PSTROBE*, and STROB) as would a traditional FPDP/TM while terminating the remaining signals as would a FPDP/RM. To use this mode StreamStor should be physically positioned at an end of the FPDP bus. Note also that the maximum useable frequency in this mode will decay more rapidly as the cumulative distance from the clock source to the data source to the data destination increases.

When configuring StreamStor as a recorder, it may be desirable to prevent a transmitter from sending data until the StreamStor recording function is fully enabled. `XLRSetDBMode` can be used to assert the FPDP NRDY* (Not Ready) signal when StreamStor is activated as a FPDP receiver. NRDY* will remain asserted until the StreamStor data recording process is ready to proceed. An example of this is:

```
XLRSetDBMode (device, FPDP_RECVMaster, SS_OPT_FPDPNRASSERT) ;
```

PSTROBE/PSTROBE* and STROB Signals

When in FPDP/TM and FPDP/RMCM modes, StreamStor will drive and terminate both the differential clock pair of PSTROBE, PSTROBE* (\pm PECL Data Strobe) and the single-ended STROB (Data Strobe) TTL clock. When in any other mode, the user will select which of the two FPDP clock sources StreamStor should use from the FPDP bus. The clock can be selected by calling `XLRSetDBMode` with the desired clock option. For example, to enable the data strobe clock (TTL):

```
XLRSetDBMode( device, FPDP_RECV, SS_OPT_FPDPSTROB ) ;
```

Refer to the FPDP ANSI standard for recommendations and observations about the use of these signals.

¹ StreamStor always provides series termination on the DATA signals as described in Permission 6.4.1 of the ANSI specification.

Chapter 6
Channel Description
and Selection

Channel Description and Selection

There are three data paths or channels that can be used to input and output data to /from the StreamStor board. These channels are: the PCI Bus, the FPDP top connector, and the FPDP front connector. A single channel or multiple channels may be selected to record from. Only one channel at a time can be selected to playback from. This section describes the commands that should be used to correctly set up the StreamStor channels for recording and playback.

For StreamStor users who have software that was written prior to SDK 7.0 and currently use the PCI Bus to transfer data to/from the StreamStor card, your software does not need to be modified to support the new channel options. That is, calls to the following API functions do not need to be added to your software since the defaults are set to single channel mode using the PCI Bus channel 0.

- `XLRSetMode`
- `XLRBindInputChannel`
- `XLRBindOutputChannel`
- `XLRClearChannels`
- `XLRSelectChannel`

Calls to these functions only need to be added if you want to use the multi-channel options or the FPDP front connector.

Channel Description

The StreamStor board currently supports three channels: the PCI Bus, the FPDP top connector, and the FPDP front connector. The PCI Bus is defined as channel 0, the FPDP top connector is defined as channel 30 and the FPDP front connector is defined as channel 31. The default channel for record and playback is the PCI Bus channel 0. There are plans to increase the number of PCI channels in the future.

Selecting an Operating Mode

The StreamStor operating mode, which can set the StreamStor board to single or multi-channel mode, should be set before binding or selecting a channel. The function `XLRSetMode` is used to set the operating mode by passing the `Mode` parameter of `SS_MODE_SINGLE_CHANNEL` to set single channel mode or `SS_MODE_MULTI_CHANNEL` for multi-channel mode. The default operating mode is `SS_MODE_SINGLE_CHANNEL`.

Binding and Selecting Channels

In single channel mode, the StreamStor board needs to know which channel to record from and which channel to playback to. The process of choosing a channel is called *binding* a channel. Binding a channel is analogous to choosing the data path. The function `XLRBindInputChannel` is used to bind a channel for input into StreamStor and the function `XLRBindOutputChannel` is used to bind a channel for output from StreamStor. These functions should be called before data is transferred to or from the StreamStor board. `XLRClearChannels` should be called to clear the default channels prior to calling `XLRBindInputChannel` and `XLRBindOutputChannel`, or these functions *may* return an error. The default channel for record and playback is the PCI Bus channel 0.

To record and playback a single channel, a call to `XLRBindInputChannel` is made, passing the parameter of the channel to record and a call to `XLRBindOutputChannel` is made passing, a parameter of the channel to playback through. To record multiple channels simultaneously, the function `XLRBindInputChannel` must be called once for each channel to be recorded. A maximum of two channels can be recorded simultaneously by the StreamStor board and only one channel can be played back at a time.

Channels that are recorded in multi-channel mode retain the channel number they were recorded on, so when a channel needs to be played back, its channel number must be selected using `XLRSelectChannel`. On playback both the data output path and channel need to be selected. The data output path is selected using `XLRBindOutputChannel` and the channel of data to be played back is selected using `XLRSelectChannel`. This method allows the data to be output on a different channel than it was recorded on.

The `XLRSelectChannel` function is also used to select a channel that future functions will act on. One example is that `XLRSelectChannel` needs to be called to select the FPDP channel before a call to `XLRSetDBMode` is made.

Example 1

The following C code shows how to set up the PCI Bus channel 0 as an input channel to record, and then read the data back through the PCI Bus channel 0. For simplicity, error handling is not shown.

```
/** include files **/
#include <stdio.h>
#include "xlrapi.h"

/** local definitions **/
#define START_ADDRESS      0x100000
```

CHAPTER 6 : CHANNEL DESCRIPTION AND SELECTION

```
void main()
{
    SSHANDLE          xlrDevice;
    S_READDESC       sRead;
    PULONG           pBuf = NULL;
    DWORDLONG        dwAddress = 0;
    XLR_RETURN_CODE  xlrStatus;

    xlrStatus = XLROpen( 1, &xlrDevice );
    ...
    // Set StreamStor mode to Single Channel
    xlrReturnCode = XLRSetMode( xlrDevice, SS_MODE_SINGLE_CHANNEL );

    // Channels must be cleared prior to binding.  XLRclearChannels
    // clears the input and the output channels.
    xlrStatus = XLRclearChannels( xlrDevice );

    // Input will be done over the PCI Bus, which is channel zero.
    xlrStatus = XLRBindInputChannel( xlrDevice, 0 );
    -
    // Select channel zero to begin recording on.
    xlrStatus = XLRSelectChannel( xlrDevice, 0 );

    // Record for a while on channel zero.
    xlrStatus = XLRRecord( xlrDevice, 0, 1 );

    printf( "Recording..." );
    ... record for a while ...
    printf( "Recording done!\n" );

    // Stop recording.
    XLRStop( hTarget );

    // Bind PCI Bus channel 0 as output channel.
    xlrStatus = XLRBindOutputChannel( xlrDevice, 0 );

    // Select Channel to read - channel 0
    xlrStatus = XLRSelectChannel( xlrDevice , 0 );

    pBuf = (PULONG)malloc( BUFFER_SIZE );

    // Build the read descriptor.
    dwAddress = START_ADDRESS;
    sRead.AddrHi = (ULONG)( START_ADDRESS << 32 );
    sRead.AddrLo = (ULONG)( START_ADDRESS );
    sRead.BufferAddr = pBuf;
    sRead.XferLength = BUFFER_SIZE;

    xlrStatus = XLRRead( xlrDevice, &sRead );

    printf( "Read Complete.\n" );

    XLRclose( xlrDevice );

    if( pBuf )
    {
```

```

        free( pBuf );
        pBuf = NULL;
    }
}

```

Example 2

The following C code shows how to set up the top FPDP connector as an input channel to record, then read the data back through the PCI Bus Channel 0. For simplicity, error handling is not shown.

```

/** include files */
#include <stdio.h>
#include "xlrapi.h"

/** local definitions */
#define TARGET_INDEX          3
#define SENDER_TOP_INDEX     1

#define START_ADDRESS         0x100000
#define TOP_SPEED              SS_PORTCLOCK_10MHZ

void main()
{
    SSHANDLE          hTarget = 0;
    SSHANDLE          hTop = 0;
    SSHANDLE          hFront = 0;
    ULONGLONG         dwPlayLength = 0;
    S_READDESC        sRead;
    PULONG            pBuf = NULL;
    DWORDLONG         dwAddress = 0;
    XLR_RETURN_CODE    xlrStatus;

    xlrStatus = XLROpen( TARGET_INDEX, &hTarget );

    xlrStatus = XLRSetMode( hTarget, SS_MODE_SINGLE_CHANNEL );

    xlrStatus = XLRClearChannels( hTarget );

    // Bind the top port (channel 30) as the input channel.
    xlrStatus = XLRBindInputChannel( hTarget, 30 );

    // Select and set FPDP options on TOP port.
    xlrStatus = XLRSelectChannel( hTarget, 30 );
    xlrStatus =
        XLRSetDBMode( hTarget, SS_FPDP_RECVMaster, SS_OPT_FPDPNRASSERT );

    // Start recording.
    xlrStatus = XLRRecord( hTarget, FALSE, TRUE );

    printf( "Recording..." );
    ... record for a while ...
    printf( "Recording done!\n" );
}

```

```

XLRStop( hTarget );

xlrStatus = XLRSelectChannel( hTarget, 30 );

// Set up to read the data we just recorded.
xlrStatus = XLRSetMode( hTarget, SS_MODE_SINGLE_CHANNEL );

xlrStatus = XLRClearChannels( hTarget );

// Bind PCI Bus channel 0 as output channel.
xlrStatus = XLRBindOutputChannel( hTarget, 0 );

// Select Channel to read - channel 30.
xlrStatus = XLRSelectChannel( hTarget, 30 );

pBuf = (PULONG)malloc( BUFFER_SIZE );

// Build the read descriptor.
dwAddress = START_ADDRESS;
sRead.AddrHi = (ULONG)( START_ADDRESS << 32 );
sRead.AddrLo = (ULONG)( START_ADDRESS );
sRead.BufferAddr = pBuf;
sRead.XferLength = BUFFER_SIZE;

// Read a buffer.
xlrStatus = XLRRead( hTarget, &sRead );

printf( "Read Complete.\n" );

XLRClose( hTarget );

if( pBuf )
{
    free( pBuf );
    pBuf = NULL;
}
}

```

Example 3

The following C code shows how to do a multi-channel recording using the top and front FPDP connectors as input channels to record then read channel 30 data back through the PCI Bus Channel 0. For simplicity, error handling is not shown.

```

/** include files */
#include <stdio.h>
#include "xlrapi.h"

/** local definitions */
#define TARGET_INDEX          3
#define FRONT_SPEED           SS_PORTCLOCK_13MHZ
#define TOP_SPEED             SS_PORTCLOCK_10MHZ
#define START_ADDRESS         0x100000

```

```

void main()
{
    SSHANDLE      hTarget = 0;
    SSHANDLE      hTop = 0;
    SSHANDLE      hFront = 0;
    ULONGLONG     dwPlayLength = 0;
    S_READDESC    sRead;
    PULONG        pBuf = NULL;
    DWORDLONG     dwAddress = 0;
    XLR_RETURN_CODE    xlrStatus;

    // Configure the target device.
    xlrStatus = XLROpen( TARGET_INDEX, &hTarget );

    // Setting target mode to Multi-Channel.
    xlrStatus = XLRSetMode( hTarget, SS_MODE_MULTI_CHANNEL );

    xlrStatus = XLRClearChannels( hTarget );

    // Bind TOP port (connector) as input channel.
    xlrStatus = XLRBindInputChannel( hTarget, 30 );

    // Bind FRONT port (connector) as input channel.
    xlrStatus = XLRBindInputChannel( hTarget, 31 );

    // Select and set FPDP options on TOP port.
    xlrStatus = XLRSelectChannel( hTarget, 30 );
    xlrStatus =
        XLRSetDBMode( hTarget, SS_FPDP_RECVMaster, SS_OPT_FPDPNRASSERT );

    // Select and set FPDP options on FRONT port.
    xlrStatus = XLRSelectChannel( hTarget, 31 );
    xlrStatus =
        XLRSetDBMode( hTarget, SS_FPDP_RECVMaster, SS_OPT_FPDPNRASSERT );

    // Start recording.
    xlrStatus = XLRRecord( hTarget, FALSE, TRUE );

    printf( "Recording..." );
    ... record for a while...
    printf( "Recording done!\n" );

    //***** Stop Recording *****
    XLRStop( hTarget );

    xlrStatus = XLRSelectChannel( hTarget, 30 );

    // Setup for Read of data just recorded on channel 30 - TOP Port.
    xlrStatus = XLRSetMode( hTarget, SS_MODE_SINGLE_CHANNEL );

    xlrStatus = XLRClearChannels( hTarget );

    // Bind PCI Bus channel 0 as output channel
    xlrStatus = XLRBindOutputChannel( hTarget, 0 );

```

CHAPTER 6 : CHANNEL DESCRIPTION AND SELECTION

```
// Select Channel to read -channel 30
xlrStatus = XLRSelectChannel( hTarget, 30 );

pBuf = (PULONG)malloc( BUFFER_SIZE );

// Set up the read descriptor.
dwAddress = START_ADDRESS;
sRead.AddrHi = (ULONG)( START_ADDRESS << 32 );
sRead.AddrLo = (ULONG)( START_ADDRESS );
sRead.BufferAddr = pBuf;
sRead.XferLength = BUFFER_SIZE;

xlrStatus = XLRRead( hTarget, &sRead );
printf( "Read Complete.\n" );

XLRClose( hTarget );

if( pBuf )
{
    free( pBuf );
    pBuf = NULL;
}
}
```

Chapter 7

Bank Switching

Bank Switching

The Big River TK200 (“TK200”) is a rack mounted StreamStor storage system. It features two hot-swappable 8-drive modules that can be used to record continuously. The bank switching feature is available only on the Big River TK200.

Bank switching is used to control drive modules in separate banks as if they were contiguous units in a recording. A *bank* is a rack containing a drive module. The TK200 has two banks, referred to as Bank A and Bank B. Each bank can hold a drive module, and each drive module can hold up to four pairs of master/slave drives for a total of eight drives. Therefore, a TK200 can support a maximum of 16 drives. You can play or record data from the drive module in one bank while the other bank is idle or dismantled.

Setting Bank Mode

The TK200 can operate in bank mode or non-bank mode. When in non-bank mode, the TK200 operates the same as a non-TK200 system; namely, the drives in the drive modules are read and written as if they were a single set.

Only StreamStor systems with a TK200 chassis support bank mode. The chassis type can be determined by calling the API function `XLRGetChassisType`. Currently, the chassis type returned is either `TK200` or `UNKNOWN_CHASSIS_TYPE`.

When in bank mode, the drives in each drive module are recorded independently. That is, a recording made on the drives on Bank A is independent of the recording made on the drives on Bank B. In this mode, you can load a single bank with a drive module or both banks with drive modules and begin recording or playback.

The API function `XLRSetBankMode` is used to enable or disable bank mode on the TK200. By default, bank mode is disabled - you must call `XLRSetBankMode` to enable it. (StreamStor PCI-816V100 and PCI-816VXF2 boards are an exception. By default, they are bank mode enabled.) To enable bank mode, the StreamStor recorder must be idle (not recording or playing data).

When a StreamStor is in bank mode, it stays in bank mode until `XLRSetBankMode` is called to take it out of bank mode or the StreamStor card is reset.

Assume both banks are loaded with drive modules. When the drive module in Bank A is full, you could switch recording to Bank B. While Bank B is

recording, you could replace the full drive module in Bank A with a new drive module. In this way, you could continue recording as long as you want, switching out full drives with empty drives indefinitely.

If bank mode is disabled, or if the chassis or board type does not support bank mode, all API functions operate on the drives as if the drives were a single device rather than two independent banks.

Selecting a Bank

Some API functions are "bank aware", which means that when the TK200 is in bank mode, the API function will be performed on the selected bank. The selected bank is identified by bank aware API functions as follows:

- If the system is not in bank mode and then `XLRSetBankMode` is called to enable it, Bank A, if it is available, is by default the selected bank. If Bank A is not available (i.e., there is no drive module in Bank A or Bank A's drive module is faulty), then Bank B, if it is available, becomes the selected bank.
- If the system is in bank mode and then `XLRSelectBank` is called, the bank specified in the `XLRSelectBank` call becomes the selected bank. It remains the selected bank until `XLRSelectBank` is called to select a different bank.
- If the system is in bank mode and the `StreamStor` is closed by calling `XLRClose`, then the next time `XLROpen` is called, it will still be in bank mode. The selected bank will be the bank that was selected at the time of the last call to `XLRClose`.

For example, assume that the `StreamStor` is in bank mode and `XLRSelectBank` has been called to select Bank B. Then `XLRRecord` is called. In this case, recording will begin on Bank B. If `XLRGetDirectory` is then called, the length returned will be the length of the recording on Bank B.

To determine which bank is selected, call `XLRGetBankStatus` and examine the selected member of the `S_BANKSTATUS` structure.

Recording a Drive Module

When the TK200 is in bank mode, API routines such as `XLRRecord` and `XLRWrite` can be used to put the recorder into record mode. If both banks contain drive modules, data will be written on the drive module in the selected bank until the drive module is full. When full, recording ceases on the selected bank. Your application may then explicitly select the other bank to resume recording.

Recording continues on the newly selected bank until its drive module, too, is full. As long as full drive modules are replaced by modules that are not full, recording can continue in this fashion, with recording alternating between the two banks, until `XLRStop` is called.

Playing back from a Drive Module

In bank mode, the standard `XLRPlayback`, `XLRRead` or `XLRReadData` functions can be used to playback or read data into memory. If both banks contain drives with data, data will be played back from the drive module in the selected bank until all data from the selected bank has been played (or a set play length is reached). Then, playback ceases on the selected bank. Your application may then select the other bank to continue playback. Playback continues on that bank until all data has been played. Playback can continue in this fashion, with data retrieval alternating between the two banks, until all data is played, a play length is reached, or `XLRStop` is called.

Labeling Drive Modules

By default, drives modules are not labeled. You can use the `XLRsetLabel` function to label idle drive modules with a null terminated string. When in non-bank mode, the label applies to the entire collection of drives that are mounted. When in bank mode, the label applies only to the drive module in the selected bank. For example, to label the drives in both banks you would:

1. Call `XLRselectBank` with `bankID` set to `BANK_A`.
2. Call `XLRsetLabel` with the desired label for Bank A.
3. Call `XLRselectBank` with `bankID` set to `BANK_B`.
4. Call `XLRsetLabel` with the desired label for Bank B.

The label can be up to `XLR_DRIVEMODULE_LABEL_LENGTH` bytes long.

Because the label is a NULL terminated string, you can "remove" a label from a drive module by calling `XLRsetLabel` with the desired label set to a null string.

You can call `XLRsetLabel` on an idle `StreamStor` to add or modify a label any time after a drive module has been selected. Labels need not be unique, i.e., the drive module in Bank A and the drive module in Bank B can have the same label.

To retrieve a label from a drive module, select the desired bank and then call `XLRgetLabel`. The buffer you read the label into must be large enough to hold the label and the NULL terminator.

Writing a User Directory

A user directory is a reserved area on a StreamStor recording that can only be written to by calling the function `XLRSetUserDir`. The user directory can be any type of data, including binary data. The user directory can be up to `XLR_MAX_UDIR_LENGTH` bytes long. When in non-bank mode, there is only one user directory. When in bank mode, each drive module can have a user directory.

Because of firmware limitations, the size of the user directory must be a multiple of eight bytes.

Writing a user directory on a bank is similar to writing a label on a bank. You first select the bank by calling `XLRSelectBank` and then call `XLRSetUserDir` to write the directory to it.

Since user directories are variable length and may or may not be NULL terminated, you must first get the user directory length before retrieving the user directory. For example, to get the user directory on Bank B, you would:

1. Call `XLRSelectBank` with *bankID* set to `BANK_B`.
2. Call `XLRGetUserDirLength` to get the length of the user directory on Bank B.
3. Call `XLRGetUserDir` to retrieve the user directory on Bank B, passing it the length that was returned by the call to `XLRGetUserDirLength`.

The Length of Drive Modules

The amount of data recorded on a drive module can be obtained by using any of the following API functions:

- `XLRGetLength` - the length is returned as a function value.
- `XLRGetDirectory` - the length is returned in the `Length` member of the `S_DIR` structure.
- `XLRGetBankStatus` - the length is returned in the `Length` member of the `S_BANKSTATUS` structure.

All three of the above functions are bank aware, which means that the length returned is the length on the selected bank.

Note that regardless of the bank mode, the length returned by the functions does not include the size of the label (if any) or the size of the user directory (if any).

Write Protecting Drive Modules

By default, drive modules are not write protected. You can use the `XLRSetsWriteProtect` function to write protect idle drive modules. When in non-bank mode, the write protection applies to the entire collection of drives that are mounted. When in bank mode, the write protection applies only to the drive module in the selected bank.

The write protection remains from recording session to recording session, even if the drive module has been removed from the system and then reinserted. Write protection can be removed by calling the function `XLRClearWriteProtect`. When in non-bank mode, the write protection will be cleared from the entire collection of drives that are mounted. When in bank mode, the write protection is cleared only from the drive module in the selected bank.

Note that the write protection is only recognized by StreamStor recorders - it is not recognized by other systems.

Erasing Drive Modules

The command `XLRErase` is used to erase data on the StreamStor recorder. When in non-banking mode, the entire collection of drives is erased. When in bank mode, the erasure applies only to the drive module in the selected bank. The drives must be idle in order to perform the erase.

There are several options to `XLRErase`. When in bank mode, note that:

- If the drive module in the selected bank is write protected, `XLRErase` will have no effect on it.
- If the `XLRErase` option `SS_OVERWRITE_DIRECTORY` is used, the user directory on the selected drive module will be deleted. The label on the selected drive module will be replaced with the default label.

Getting Bank Status

Use `XLRGetBankStatus` to get the status of selected bank. This function will return the selected bank's status in a structure of type `S_BANKSTATUS`. For details on this structure, see the structure definition at the end of the Function Reference section of this manual.

Replacing a Drive Module

As drive modules fill up during a recording, you may want to replace the full modules with empty (or otherwise writable) drive modules. This becomes necessary, for instance, when Bank A becomes full, recording is in progress

on Bank B and a switch will be done back to Bank A. In this case, follow these steps to replace the full drive module with a new module:

1. Power off the bank containing the full drive module. When successfully powered down, all lights on the bank will go off.
2. Once the lights are off, remove the full drive module from the bank.
3. Put the new (write-enabled) drive module in the empty bank.
4. Power up the bank containing the new drive module. On power up, StreamStor will initialize the drive module. When the initialization has completed the READY light on the bank will light.

The same procedure can be applied to playback. If a recording spans more than two drive modules, when playback switches to the second drive module, once all data on the first drive module has been played, you can replace it with the third module in the set, etc.

You can also use the functions `XLRMountBank` and `XLRDismountBank` to mount and dismount banks.

Chapter 8

Drive Partitioning

Drive Partitioning

Partitioning allows you to logically divide the StreamStor drives into isolated sections. The partitioning feature is included on a variety of StreamStor controllers. The hardware manual for your StreamStor controller or daughter board will indicate if partitioning is supported on it and will provide any other model-specific details.

The StreamStor can operate with or without partitions. By default, the drives are not partitioned. When the drives are not partitioned, they are operated upon as if they were a single unit. If the drives are partitioned, StreamStor operations are performed on the currently selected partition.

Creating a Partition

A partitioned system has one or more partitions and an undefined area that has not yet been partitioned. The API function `XLRPartitionCreate` is used to create a partition. You pass the function the length of the partition you want to create. The length is specified in pages, where a page is 4096 bytes. The function will attempt to create a partition of approximately the requested size. The actual size of the partition that is created is determined by the state of the disks and other internal boundary restrictions. The API function `XLRGetPartitionInfo` will return the actual size of the partition that was created in the `PartitionCapacity` member of the `S_PARTITIONINFO` structure.

When a partition is created, it is assigned a partition number. Partition numbers start at 0 (zero) and increment up to 256.

If the StreamStor has data recorded on it that was written in a non-partitioned mode, that data must first be erased before you can create any partitions.

Selecting a Partition

The API function `XLRPartitionSelect` is used to select the partition that is to be used for subsequent StreamStor operations. To select a partition, call `XLRPartitionSelect`, specifying the partition number that was assigned to it when it was created.

Some examples of partition-specific operations are:

- `XLRRecord` records only on the selected partition.
- `XLRSetWriteProtect` applies write protection only to the selected partition.

- `XLRERASE` with any option (other than the option to destroy all partitions), erases the data only in the selected partition.
- `XLRGetDirectory` returns information that pertains only to the selected partition. For instance, the `Full` structure member of `S_DIR` will be set to `TRUE` if the selected partition is full.
- `XLRSetLabel` applies the requested label only to the selected partition.

If a partition has not been selected by calling `XLRPartitionSelect`, then partition 0 (zero) will be selected by default.

See the section "Bank Mode and Partitioning" in this chapter for details on how the selected bank works in conjunction with the selected partition.

Getting Partition Information

The API function `XLRGetPartitionInfo` is used to retrieve information from the `StreamStor` about the currently selected partition. To obtain this information, you pass `XLRGetPartitionInfo` a pointer to a structure of type `S_PARTITIONINFO`. The structure is returned, populated with the total number of partitions on the `StreamStor`, the partition number of the selected partition, the capacity of the partition, etc. Full details of the `S_PARTITIONINFO` structure can be found at the end of the `Function Reference` chapter.

Bank Mode and Partitioning

Partitioning can be used in conjunction with bank mode. When in bank mode, you can optionally partition one or both modules. In practice, when you are using bank mode, you will probably always want to partition both modules.

If in bank mode, the selected bank and the selected partition are used to determine where subsequent `StreamStor` operations are performed. For example, if you call `XLRSelectBank` to select Bank B, then call `XLRPartitionSelect` to select partition six, if you should then call `XLRSetLabel`, that label will be applied only to partition six on Bank B.

Note that if you are in bank mode and are using partitions, the bank modes `SS_BANK_AUTO_ON_FULL` and `SS_BANK_MODE_AUTO_ON_SYNC` are not allowed. The only way to begin operations on a different bank is to explicitly select the bank to be used.

Recording using Partitions

If a StreamStor has any partitions on it, subsequent operations on the StreamStor will be partition-specific. The following example illustrates this.

Assume you had previously created several partitions and that partition three had been created as one megabyte long. If you then select partition three with `XLRPartitionSelect`, and then begin a recording with wrap mode disabled, that data will be recorded only in partition three. When one megabyte has been recorded, that partition is "full" and recording will cease. To begin recording on partition number four, you would first have to select it.

Using the same partitioning described above, if recording was started with wrap mode enabled, then once partition three had been recorded to its capacity, the recording would "wrap around" and start recording over the previously written data in partition three.

In a similar fashion, to play back recorded data you must first select the partition to be played.

Removing Partitioning

Once a system has been partitioned, it remains partitioned until the system is erased using the `XLRErase` function with the `SS_OVERWRITE_PARTITION` option set. `XLRErase` will erase all data, partitions, user directories and labels. If in bank mode, the erasure will be applied to the currently selected bank.

Reusing Partitions

You can "erase" the data on a specific partition and reuse it. Recall that if you call `XLRRecord`, it will cause new data to overwrite existing data. If you are in bank mode, a call to `XLRRecord` will erase the currently selected bank. Similarly, if you are using partitioning, a call to `XLRRecord` will erase the currently selected partition. So, to erase a specific partition, select the partition using `XLRPartitionSelect`, then call `XLRRecord` immediately followed by `XLRStop`.

Example

The following C code shows some of the features of partitioning.

```
//
// This example demonstrates some of the partitioning features of
// the StreamStor.
//
#include <stdio.h>
```

CHAPTER 8 : DRIVE PARTITIONING

```
#include <stdlib.h>
#include <string.h>
#include "xlrapi.h"

#ifdef TRUE
#define TRUE 1
#define FALSE 0
#endif

#define PAGE_SIZE 4096

int main( int argc, char *argv[] )
{
    SSHANDLE          xlrDevice;
    S_PARTITIONINFO   pInfo;
    UINT              k;
    UINT              pSizeInBytes;
    char               errorMessage[XLR_ERROR_LENGTH];
    char               label[XLR_LABEL_LENGTH];

    if (XLROpen (1,&xlrDevice) != XLR_SUCCESS) {
        printf ("Could not open StreamStor.\n");
        exit(1);
    }

    //
    // See if this StreamStor was partitioned. By default partition zero
    // is selected.
    //
    if (XLRGetPartitionInfo(xlrDevice , &pInfo) != XLR_SUCCESS) {
        printf ("Could not get partition information.\n");
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error: %s\n", errorMessage);
        XLRclose(xlrDevice);
        exit(1);
    }

    if (pInfo.Partitioned == TRUE) {
        printf ("This system is partitioned.  It has %u partitions.\n",
            pInfo.NumPartitions);
    }
    else {
        printf ("This system is not partitioned.\n");

        //
        // The first time you create a partition, the device must
        // be empty.
        //
        if (XLRerase (xlrDevice, SS_OVERWRITE_NONE) != XLR_SUCCESS) {
            printf ("Could not erase system.");
            XLRGetErrorMessage(errorMessage, XLRGetLastError());
            printf ("Error: %s\n", errorMessage);
            XLRclose(xlrDevice);
            exit(1);
        }
    }
}
```

CHAPTER 8 : DRIVE PARTITIONING

```
//
// Create two partitions of different sizes.
//
for (k=0; k<2; k++) {
    pSizeInBytes = (PAGE_SIZE*100) * (k+1);
    printf
        ("Creating partition %u with size %u bytes = %u pages.\n",
         k, pSizeInBytes, pSizeInBytes/PAGE_SIZE);
    if (XLRPartitionCreate(xlrDevice, pSizeInBytes)
        != XLR_SUCCESS) {
        printf ("Could not create partition %u.\n", k);
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error: %s\n", errorMessage);
        XLRclose(xlrDevice);
        exit(1);
    }

    //
    // Select the partition that is to be labeled.
    //
    if (XLRPartitionSelect(xlrDevice, k) != XLR_SUCCESS) {
        printf ("Could not select partition %u.\n", k);
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error is %s\n", errorMessage);
        XLRclose(xlrDevice);
        exit(1);
    }

    //
    // Label the partition that is selected.
    //
    sprintf (label, "Partition_%u\n", k);
    if (XLRsetLabel(xlrDevice, label, (UINT) strlen(label)) !=
        XLR_SUCCESS) {
        printf ("Could not label partition %u.\n", k);
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error is %s\n", errorMessage);
        XLRclose(xlrDevice);
        exit(1);
    }
}

//
// Print information about the two partitions.
//
for (k=0; k< 2; k++) {
    if (XLRPartitionSelect(xlrDevice, k) != XLR_SUCCESS) {
        printf ("Could not select partition %u.\n", k);
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error is %s\n", errorMessage);
        XLRclose(xlrDevice);
        exit(1);
    }

    if (XLRGetPartitionInfo(xlrDevice , &pInfo) != XLR_SUCCESS) {
        printf ("Could not get partition information.\n");
    }
}
```

CHAPTER 8 : DRIVE PARTITIONING

```
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error:  %s\n", errorMessage);
        XLRClose(xlrDevice);
        exit(1);
    }
    printf ("Selected Partition: %u\n", pInfo.SelectedPartition);
    printf ("\tTotal Pages: %u\n", pInfo.PartitionCapacity);

    if (XLRGetLabel(xlrDevice,label) != XLR_SUCCESS) {
        printf ("Could not get label from partition %u.\n", k);
        XLRGetErrorMessage(errorMessage, XLRGetLastError());
        printf ("Error is %s\n", errorMessage);
        XLRClose(xlrDevice);
        exit(1);
    }
    printf ("\tLabel: %s\n", label);
}

printf ("Number of Partitions: %u\n", pInfo.NumPartitions);
printf ("Pages in partitions: %u\n", pInfo.SpaceAllocated);
printf ("Pages available for partitioning: %u\n",
        pInfo.SpaceAvailable);

//
// Erase data, remove partitions, labels, etc.
//
XLRerase (xlrDevice, SS_OVERWRITE_PARTITION);

//
// System should now be unpartitioned.
//
if (XLRGetPartitionInfo(xlrDevice , &pInfo) != XLR_SUCCESS) {
    printf ("Could not get partition information.\n");
    XLRGetErrorMessage(errorMessage, XLRGetLastError());
    printf ("Error:  %s\n", errorMessage);
    XLRClose(xlrDevice);
    exit(1);
}
if (pInfo.Partitioned == TRUE) {
    printf ("Error - this system should not be partitioned now!");
}
else {
    printf ("\nThis system is not partitioned anymore.\n");
}
}

XLRClose(xlrDevice);
exit(0);
}
```

CHAPTER 8 : DRIVE PARTITIONING

Output from this program would look something like this:

```
This system is not partitioned.
Creating partition 0 with size 409600 bytes = 100 pages.
Creating partition 1 with size 819200 bytes = 200 pages.
Selected Partition: 0
    Total Pages: 100
    Label: Partition_0

Selected Partition: 1
    Total Pages: 200
    Label: Partition_1

Number of Partitions: 2
Pages in partitions: 300
Pages available for partitioning: 134516582

This system is not partitioned anymore.
```

Chapter 9

Forking and Passthru

Forking And Passthru

StreamStor cards have the capability of real time “passing” and “forking” of data streams.

Overview

Data “forking” is the simultaneous recording and output of data. This is a real time operation which allows for the manipulation of data as well as recording of that same data stream simultaneously. Forking requires input from one source (PCI bus, top or front FPDP connector) and a *different* output channel. For example, data could be received over the front FPDP port, recorded to disk, and sent out the top FPDP port.

“Passthru” is the input of data over 1 channel (PCI bus, top or front FPDP port) and the simultaneous output (*over a different channel*) of that data *without* being recorded to disk. When StreamStor is operating in passthru mode, no disk drives are required; any drives that are connected are ignored by StreamStor.

☞ **NOTE:** **Both passthru and fork modes are REALTIME ONLY. Thus, the data must go out at the same speed as it is coming in. If not, an overflow condition will be signaled (see Overflow section below) and the data order OF THE OUTPUT STREAM can no longer be guaranteed. However, in forking mode, even an overflow condition WILL NOT JEPORDIZE THE DISK RECORDING in any way.**

Forking

Forking is used in situations where the data must be used in real-time and recorded to disk simultaneously. Forking mode is set by a call to `XLRSetMode` using the `SS_MODE_FORK` parameter for the mode. Input and output streams are set by calls to `XLRBindInputChannel` and `XLRBindOutputChannel`.

☞ **NOTE:** *The bound input and output channels must be different.*

A call to either `XLRRecord` or `XLRAppend` will start the data flow. Make sure that the FPDP port(s) are configured before record/append is called.

Passthru

Data “passthru” is the simultaneous input and real-time output of data. Passthru is used in situations where the data must be used in real-time and

recording that data is not necessary or desired. Passthru is configured the same way forking is except that `XLRSetMode` is passed the `SS_MODE_PASSTHRU` parameter. `XLRRecord` is called to start data flowing even though no disk recording takes place.

Output over the PCI bus

Using the PCI bus as an output channel differs from single channel reads in that calls to `XLRReadFIFO` are required. `XLRReadFIFO` retrieves data from `StreamStor` to the user provided buffer (similar in operation to `XLRReadData`). `XLRReadFIFO` first ensures that the amount of data available in `StreamStor`'s FIFO is greater than or equal to the amount of data requested. If there is not enough data present, `XLRReadFIFO` will wait up to 5 seconds for enough data to complete the request. Should not enough data be present after 5 seconds, `XLRReadFIFO` will return status `XLR_FAIL`. Subsequent calls to `XLRGetLastError` and `XLRGetErrorMessage` will yield a “no data” error.

☞ **NOTE:** *A “no data” error does not necessarily mean that there are 0 bytes to be read, only that there are fewer bytes than the requested size.*

Checking the FIFO length

The `StreamStor` SDK provides the `XLRGetFIFOLength` function to provide the real time ability to check the amount of data that is available for output. This function returns a 64 bit integer that is the number of bytes available for reading at that time. This function is provided for informational purposes and is primarily used in the situation where input data flow is slow enough that the `XLRReadFIFO` timeout of 5 seconds is not adequate. In that case, user applications can make calls to `XLRGetFIFOLength` to ensure there is enough data present before the call `XLRReadFIFO`.

Overflows

Data forking and passthru operate in a real time fashion. If data is coming in faster than it is leaving, `StreamStor`'s on board RAM buffer will eventually fill and an overflow condition will arise. Overflow conditions are signaled by the `Overflow` member of the `S_DEVSTATUS` structure. This structure is filled by calls to `XLRGetDeviceStatus`. See the function reference for more information.

☠ **CAUTION:** *Once an overflow condition arises, the integrity and order of output data can no longer be guaranteed. The only way to “recover” from an overflow situation is to stop and restart `StreamStor`.*

☞ **NOTE:** *In forking mode, the recording to disk will continue accurately and uninterrupted – only the order of the output data stream will be inaccurate.*

Chapter 10

Technical Support

(303) 485-2721

support@conduant.com

www.conduant.com/support

Technical Support

Conduant wants to be sure that your StreamStor system works correctly and stays working correctly. In the unlikely event, however, that you are unable to get your new system to work properly, or if a working system ceases to function, we will do all that we can to get your system back online.

Solving the problem is largely a matter of data collection and steps that must be taken one at a time. In order for us to better serve you, we ask that you take the time to perform the following steps prior to calling us. This way, you can provide us with the most meaningful information possible that will help us solve the problem.

Is the problem one that obviously requires replacement parts due to physical damage to the system? If yes, then please gather the information described below and report the problem to tech support, by phone or through the Conduant web site.

Have you confirmed that no cabling has been inadvertently disconnected or damaged while working around the equipment?

Is the card properly seated in the PCI slot?

Do all the disk drives have good power connections and voltages?

Does the confidence test sscfg.exe (on Windows) or ssopen/ sstest (on Linux) run OK?

Has the software installation been corrupted? Try re-installing software.

Have you checked the Conduant web site for technical bulletins?

Have you recently installed a new Linux kernel or compiler or a new Windows Service Pack?

If the above steps did not resolve the problem, then please call Technical Support or open a support ticket. To open a support ticket, go to www.conduant.com, click on “Support” and then click on “Submit a ticket.”

Please provide the following information:

- StreamStor Card Serial Number
- Software Revision(s)
- Configuration (816XF, 816XF2, disk drive model numbers, etc.)

- Description of third party equipment that StreamStor is working with (i.e. Manufacturer and model numbers, etc.)
- Description of third party software being used with StreamStor
- Computer model and type (Pentium, Pentium II, etc.)
- Operating system version.

We will do all that we can to resolve the problem as quickly as possible.

Contacting Technical Support

E-mail: support@conduant.com

Phone: (303) 485-2721

Fax: (303) 485-5104

Web: www.conduant.com

Mail: Conduant Corporation

Technical Support

1501 South Sunset Street, Suite C

Longmont, CO 80501

Appendix A – Error Codes

If you are experiencing one of these errors and are unable to determine the cause, please contact Conduant technical support for assistance.

Number	Error Title	Description
2	XLR_ERR_NODEVICE	StreamStor device was not found in system.
3	XLR_ERR_NOINFO	Undefined error occurred.
4	XLR_ERR_WDOPEN	Cannot open device driver.
5	XLR_ERR_SYSERROR	The controller reported a system error.
6	XLR_ERR_NOXLR	No StreamStor cards located.
7	XLR_ERR_INVALID_CMD	An invalid command was received by the controller.
8	XLR_ERR_HANDLE	Invalid handle.
9	XLR_ERR_DMAREADFAIL	A DMA read failure occurred.
10	XLR_ERR_SYSTATUS	Request is incompatible with current system status.
11	XLR_ERR_NOCMDSTATUS	The command did not complete. Communication with controller timed out.
12	XLR_ERR_DMAINCOMPLETE	The data transfer timed out and did not complete.
13	XLR_ERR_APPSTART	The controller failed to initialize RAM application.
14	XLR_ERR_OUTOFMEMORY	The DLL failed to allocate sufficient memory.
15	XLR_ERR_WIN32FAIL	A Win32 API failure occurred.
16	XLR_ERR_WRITENOTACTIVE	System not ready to receive data.
17	XLR_ERR_WDVERSION	Incorrect driver version detected.
18	XLR_ERR_OPENHANDLE	Device reference by handle already opened.
19	XLR_ERR_INVALIDINDEX	Invalid card index value.
20	XLR_ERR_DEVICELOCK	Could not lock device for exclusive access.
21	XLR_ERR_DETECTCARD	Card configuration invalid.
22	XLR_ERR_BUFLOCK	Could not lock user memory buffer.
23	XLR_ERR_READFAIL	Data read error.
24	XLR_ERR_WRITERAM	Firmware write to device memory

APPENDIX A - ERROR CODES

		failed.
101	XLR_ERR_INVALID_LENGTH	An invalid or unaligned transfer length was requested (must be 64 bit aligned).
102	XLR_ERR_SYSBUSY	System is busy. Use XLRStop to before sending other commands.
103	XLR_ERR_CMDFAIL	The controller has failed to execute the command.
104	XLR_ERR_FILENOTFOUND	A required file was not found.
105	XLR_ERR_LOADKEY	A required registry key was not found.
106	XLR_ERR_DLDCHECKSUM	A required file is corrupted or upload failed.
107	XLR_ERR_DRVFAIL	A disk drive is failing to respond.
108	XLR_ERR_NODRIVER	Device driver not found or device already open.
109	XLR_ERR_FIFO_INACTIVE	Invalid command, FIFO inactive.
110	XLR_ERR_INVALIDDVR	An unconfigured or invalid VR was selected.
111	XLR_ERR_NOTENABLED	Optional feature not enabled.
112	XLR_ERR_OUTOFRANGE	Request was not in the recorded data range.
113	XLR_ERR_NOTINFIFO	Command valid only in FIFO mode.
114	XLR_ERR_KERNELMEM	Unable to allocate kernel memory.
115	XLR_ERR_INTENABLE	Unable install device interrupt.
116	XLR_ERR_READCOLLISION	Attempt to start multiple reads from single thread.
117	XLR_ERR_READIDLE	Attempted to check status on non-existent read request.
118	XLR_ERR_FIFODRIVES	Current drive configuration incompatible with FIFO mode.
119	XLR_ERR_FWVERSION	Hardware firmware incompatible with API version.
120	XLR_ERR_OSFAIL	A system call failed.
121	XLR_ERR_THREADCREATE	Process thread creation failed.
122	XLR_ERR_EXPECTEDDISKS_MATCH	The number of expected disks doesn't equal the actual number of disks.
123	XLR_BOARDTYPE	Unknown board type found.
124	XLR_ERR_FULL	Insufficient disk space.
127	XLR_ERR_INVOPT	Invalid option value.
142	XLR_ERR_INVALID_PORTMODE	Port in wrong mode for this operation.
143	XLR_ERR_NOAPPEND	Attempt to delete non-existent append.
144	XLR_ERR_EMPTY	No data.
145	XLR_ERR_INVALID_BANK	Invalid bank name specified.
146	XLR_ERR_NOTINBANKMODE	Command only valid in bank mode.
148	XLR_ERR_DRIVEMODULE	Drive module is not ready.

APPENDIX A - ERROR CODES

	NOTREADY	
153	XLR_ERR_CANNOT_RECOVER_DATA	No recovery of data possible.
154	XLR_ERR_NO_RECOVERABLE_DATA	No recoverable data.
155	XLR_ERR_BAD_DISKSET	A disk is missing from a recording or a disk is mounted that was not part of the set when the recording was originally made.
156	XLR_ERR_INVALID_PLAY_LENGTH	Playback length is beyond the end of the recording or is not aligned on an eight-byte boundary.
157	XLR_ERR_INVALID_WDLICENSE	Invalid driver license.
158	XLR_ERR_WRITE_PROTECTED	Command invalid on write protected drive modules.
159	XLR_ERR_MAX_CARDS	Maximum number of StreamStor cards exceeded.
160	XLR_ERR_DRVFAIL_BUS0_MASTER	Master drive on Bus 0 missing or failing.
161	XLR_ERR_DRVFAIL_BUS0_SLAVE	Slave drive on Bus 0 missing or failing.
162	XLR_ERR_DRVFAIL_BUS1_MASTER	Master drive on Bus 1 missing or failing.
163	XLR_ERR_DRVFAIL_BUS1_SLAVE	Slave drive on Bus 1 missing or failing.
164	XLR_ERR_DRVFAIL_BUS2_MASTER	Master drive on Bus 2 missing or failing.
165	XLR_ERR_DRVFAIL_BUS2_SLAVE	Slave drive on Bus 2 missing or failing.
166	XLR_ERR_DRVFAIL_BUS3_MASTER	Master drive on Bus 3 missing or failing.
167	XLR_ERR_DRVFAIL_BUS3_SLAVE	Slave drive on Bus 3 missing or failing.
168	XLR_ERR_DRVFAIL_BUS4_MASTER	Master drive on Bus 4 missing or failing.
169	XLR_ERR_DRVFAIL_BUS4_SLAVE	Slave drive on Bus 4 missing or failing.
170	XLR_ERR_DRVFAIL_BUS5_MASTER	Master drive on Bus 5 missing or failing.
171	XLR_ERR_DRVFAIL_BUS5_SLAVE	Slave drive on Bus 5 missing or failing.
172	XLR_ERR_DRVFAIL_BUS6_MASTER	Master drive on Bus 6 missing or failing.
173	XLR_ERR_DRVFAIL_BUS6_SLAVE	Slave drive on Bus 6 missing or failing.
174	XLR_ERR_DRVFAIL_BUS7_MASTER	Master drive on Bus 7 missing or failing.
175	XLR_ERR_DRVFAIL_BUS7_SLAVE	Slave drive on Bus 7 missing or failing.

APPENDIX A - ERROR CODES

176	XLR_ERR_NOTIN_RECMODE	Command only valid when in record mode.
177	XLR_ERR_EXT_TO_PCI_OVERFLOW	External port to PCI overflow.
178	XLR_ERR_INVALID_INTERFACE	Command is not available for the currently in use interface (PCI bus, Ethernet, or Serial port).
179	XLR_ERR_INVALID_RETURN_FORMAT	Data returned from command is formatted incorrectly (Ethernet and Serial port interfaces only).
180	XLR_ERR_INVALID_CHANNEL	The channel being selected or bound is invalid.
181	XLR_ERR_INVALID_OP_ON_CHANNEL	Operation is not permitted on this channel.
182	XLR_ERR_USE_SELECT_CHANNEL	SS_OPT_FPDPEXTCONN is no longer valid for selecting the front FPDP port. XLRSelectChannel must be used.
183	XLR_ERR_INVALID_SYSTEM_MODE	Requested mode is invalid.
184	XLR_ERR_TOO_MANY_CHANNELS	Only 1 input or output channel is allowed in this mode.
185	XLR_ERR_NO_INPUT_CHANNELS	Must have at least 1 input channel.
186	XLR_ERR_NO_OUTPUT_CHANNELS	Must have at least 1 output channel.
187	XLR_ERR_NOT_VALID_IN_MULTICHANNEL	Operation not valid in multichannel mode.
188	XLR_ERR_PARTITION_SIZE	Partition size must be multiple of page size.
189	XLR_ERR_INVALID_PARTITION	Invalid partition.
190	XLR_ERR_TOO_MANY_PARTITIONS	Only 256 partitions are permitted.
191	XLR_ERR_NOT_EMPTY	System must be empty for this command.
192	XLR_ERR_UNKNOWN_DIRECTORY_VERSION	The directory version found is newer than the current firmware can handle.
193	XLR_ERR_DATA_INTEGRITY	Data integrity check failed.
300	XLR_ERR_PORT_NOT_FOUND	Port is unavailable (Serial/Ethernet interfaces only).
301	XLR_ERR_PORT_ACCESS_DENIED	Port access is denied (Serial/Ethernet interfaces only).
302	XLR_ERR_PORT_TIMEOUT	Port operation has timed out.
303	XLR_ERR_CONNECT_REFUSED	Connection refused by target.

End of Document